


Telecom Grounding Busbar

Data Solutions



CERTIFICATIONS



VLASTNOSTI

Meets TIA-607-C and TIA-607-D conforms to BICSI® recommendations

Complies with NEMA® standards

Accepts two hole lugs with 5/16" or 7/16" bolt holes (hardware not included)

Telecom grounding busbar splice kits are available to extend the length of the busbar

SPECIFIKACE

Thickness (T): 6.35mm

Width (W): 50.8mm

Materiál: Copper

Table 1/2


Katalogové číslo	Tin Plating	Length 1 (L1)	Length 2 (L2)	Hole Size 1 (HS1)	Hole Size 1 Number of Pairs	Hole Size 2 (HS2)

TGBA29L18PT	Yes	737mm	457mm	8mm	18	11mm
TGBA12L06PT	Yes	305mm	229mm	8mm	6	11mm
TGBA12L06P	No	305mm	229mm	8mm	6	11mm
TGBA20L12PT	Yes	508mm	229mm	8mm	12	11mm
TGBA24L14P	No	610mm	457mm	8mm	14	11mm
TGBA24L14PT	Yes	610mm	457mm	8mm	14	11mm

Table 2/2

Katalogové číslo	Hole Size 2 Number of Pairs	A	B	C
TGBA29L18PT	5	25.4mm	28.6mm	15.9mm
TGBA12L06PT	3	25.4mm	28.6mm	15.9mm
TGBA12L06P	3	25.4mm	28.6mm	15.9mm
TGBA20L12PT	3	25.4mm	28.6mm	15.9mm
TGBA24L14P	5	25.4mm	28.6mm	15.9mm
TGBA24L14PT	5	25.4mm	28.6mm	15.9mm

DIAGRAMS



UPOZORNĚNÍ

Produkty nVent musí být instalovány a používány pouze tak, jak je uvedeno v instrukčních listech a materiálech pro školení nVent. Instrukční listy jsou k dispozici na www.nvent.com a od vašeho zástupce zákaznického servisu nVent. Nesprávná instalace, zneužití, nesprávné použití nebo jiný nedostatek úplného dodržování pokynů a varování nVent může způsobit selhání produktu, poškození majetku, vážné zranění osob a smrt a/nebo zrušit vaši záruku.



Naše portfolio silných značek:

CADDY ERICO HOFFMAN ILSCO SCHROFF TRACHTE