

Socket Strip, UTE

Modular, compact PDU with many function elements. Using a 1 U by 1 U aluminum chassis the PDU can easily be integrated in a rack with UTE outlets.



CERTIFICATIONS



VLASTNOSTI

230 V, 16 A

In accordance with NFC 61-303

Socket strip with UTE sockets

Mounting height 1 U

Horizontal or vertical mounting

Connecting cable 2 m, with SCHUKO/UTE plug

Socket strips can be rotated through all four directions (in 90° increments) during installation

SPECIFIKACE

Materiál: Hliník; Polyamide

Barva: Grey

Product Type: Socket Strip

Table 1/2

| Katalogové číslo | Typ zásuvky | Socket Quantity | Switched Outlets | Napětí střídavé | Function | Množství v balení |
|------------------|-------------|-----------------|------------------|-----------------|----------|-------------------|
| 60110-226 | UTE | 12 | Yes | 230V | | 1 |

| Katalogové číslo | Typ zásuvky | Socket Quantity | Switched Outlets | Napětí střídavé | Function | Množství v balení |
|------------------|-------------|-----------------|------------------|-----------------|--|-------------------|
| 60110-222 | UTE | 12 | No | 230V | | 1 |
| 60110-221 | UTE | 9 | No | 230V | | 1 |
| 60110-267 | UTE | 6 | No | 230V | Transient Protection, Mains Suppression Filter | 1 |
| 60110-223 | UTE | 15 | No | 230V | | 1 |
| 60110-224 | UTE | 19 | No | 230V | | 1 |
| 60110-225 | UTE | 8 | Yes | 230V | | 1 |
| 60110-231 | UTE | 6 | No | 230V | Fault Current Protection, Overcurrent Protection | 1 |
| 60110-227 | UTE | 8 | No | 230V | Transient Protection | 1 |
| 60110-228 | UTE | 6 | No | 230V | Overcurrent Protection | 1 |
| 60110-220 | UTE | 4 | No | 230V | | 1 |
| 60110-230 | UTE | 6 | No | 230V | Fault Current Protection | 1 |
| 60110-229 | UTE | 7 | No | 230V | Mains Suppression Filter | 1 |

Table 2/2

| Katalogové číslo | Hloubka | Povrchová úprava | Length |
|------------------|---------|------------------|---------|
| 60110-226 | 44mm | Anodized | 947.5mm |
| 60110-222 | 44mm | Anodized | 947.5mm |
| 60110-221 | 44mm | Anodized | 438.5mm |
| 60110-267 | 44mm | Anodized | 438.5mm |
| 60110-223 | 44mm | Anodized | 1202mm |
| 60110-224 | 44mm | Anodized | 1753mm |
| 60110-225 | 44mm | Anodized | 438.5mm |
| 60110-231 | 88mm | Anodized | 438.5mm |
| 60110-227 | 44mm | Anodized | 438.5mm |
| 60110-228 | 75mm | Anodized | 438.5mm |
| 60110-220 | 44mm | Anodized | 210mm |
| 60110-230 | 88mm | Anodized | 438.5mm |

| Katalogové číslo | Hloubka | Povrchová úprava | Length |
|------------------|---------|------------------|---------|
| 60110-229 | 44mm | Anodized | 438.5mm |

DALŠÍ PODROBNOSTI O PRODUKTU

Please order bracket for vertical mounting separately.

UPOZORNĚNÍ

Produkty nVent musí být instalovány a používány pouze tak, jak je uvedeno v instrukčních listech a materiálech pro školení nVent. Instrukční listy jsou k dispozici na www.nvent.com a od vašeho zástupce zákaznického servisu nVent. Nesprávná instalace, zneužití, nesprávné použití nebo jiný nedostatek úplného dodržování pokynů a varování nVent může způsobit selhání produktu, poškození majetku, vážné zranění osob a smrt a/nebo zrušit vaši záruku.

North America

All locations
+1.763.422.2661
Chat with us:
nvent.com/schroff

Europe

Straubenhardt, Germany
+49.7082.794.0
Betschdorf, France
+33.3.88.90.64.90
Warsaw, Poland
+48.22.209.98.35
Assago, Italy
+39.02.932.7141
Chat with us:
nvent.com/schroff

Asia

Shanghai, China
+86.21.2412.6943
Qingdao, China
+86.532.8771.6101
Singapore
+65.6768.5800
Shin-Yokohama, Japan
+81.45.476.0271
Chat with us:
nvent.com/schroff

Middle East & India

Dubai, United Arab Emirates
+971.4.378.1700
Bangalore, India
+91.80.6715.2001
Istanbul, Turkey
+90.216.250.7374
Chat with us:
nvent.com/schroff



Naše portfolio silných značek:

CADDY ERICO HOFFMAN ILSCO SCHROFF TRACHTE