

Bolt Expansion Anchor



CERTIFICERINGER



FUNKTIONER

Heavy duty wedge anchor

For cracked and non-cracked concrete

Fire resistance class R30-R120 for design of anchorages under exposure to fire

Approved for use in seismic design category C1 & C2 (for Drill Bit Diameters 8 mm and greater)

SPECIFIKATIONER

Table 1/2

Katalognummer	Artikelnummer	Materiale	Finish	Thread Size (TS)	Length (L)	Embedment Depth
SABM8050S6	401151	Stainless Steel 316 (EN 1.4401)		M8	115mm	55 mm
SABM8050	400409	Stål	Electrogalvaniz ed	M8	115mm	55 mm
SABM8010	400408	Stål	Electrogalvaniz ed	M8	75mm	55 mm


Katalognummer	Artikelnummer	Materiale	Finish	Thread Size (TS)	Length (L)	Embedment Depth
SABM10010S6	401152	Stainless Steel 316 (EN 1.4401)		M10	90mm	68 mm
SABM10010	400410	Stål	Electrogalvaniz ed	M10	90mm	68 mm
SABM10050S6	401153	Stainless Steel 316 (EN 1.4401)		M10	135mm	68 mm
SABM10050	400411	Stål	Electrogalvaniz ed	M10	135mm	68 mm
SABM12015	402170	Stål	Electrogalvaniz ed	M12	110mm	80 mm
SABM12050	401158	Stål	Electrogalvaniz ed	M12	150mm	80 mm
SABM16025	402171	Stål	Electrogalvaniz ed	M16	145mm	97 mm
SABM20030	402446	Stål	Electrogalvaniz ed	M20	167mm	114 mm

Table 2/2

Katalognummer	Artikelnummer	A	Drill Bit Diameter
SABM8050S6	401151	49 mm	8mm
SABM8050	400409	49 mm	8mm
SABM8010	400408	9 mm	8mm
SABM10010S6	401152	10 mm	10mm
SABM10010	400410	10 mm	10mm
SABM10050S6	401153	55 mm	10mm
SABM10050	400411	55 mm	10mm
SABM12015	402170	14 mm	12mm
SABM12050	401158	54 mm	12mm
SABM16025	402171	28 mm	16mm
SABM20030	402446	32 mm	20mm

Characteristic Axial Loads from ETA-12/0397		
Part Number	Cracked Concrete C20/25	Non-Cracked Concrete C20/25
SABM8010	2.4 kN	3.6 kN
SABM8050	2.4 kN	3.6 kN
SABM10010	4.3 kN	7.6 kN
SABM10050	4.3 kN	7.6 kN
SABM12015	7.6 kN	11.9 kN
SABM12050	7.6 kN	11.9 kN
SABM16025	11.9 kN	16.7 kN
SABM20030	14.3 kN	23.8 kN
SABM8010S6	2.4 kN	4.3 kN
SABM8050S6	2.4 kN	4.3 kN
SABM10010S6	4.3 kN	7.6 kN
SABM10050S6	4.3 kN	7.6 kN

DIAGRAMS



ADVARSEL

nVent-produkter skal kun installeres og anvendes som angivet i nVents produktvejledninger og træningsmaterialer. Vejledninger er tilgængelige på www.nvent.com og hos din nVent kundeservicerepræsentant. Forkert installation, misbrug, fejlanvendelse eller anden undladelse af fuldt ud at følge nVents instruktioner og advarsler kan medføre funktionsfejl, materielle skader, alvorlige personskader eller død og/eller ugyldiggøre din garanti.

North America

+1.800.753.9221

Option 1 – Customer Care

Option 2 – Technical

Support

Europe

Netherlands:

+31 800-0200135

France:

+33 800 901 793

Europe

Germany:

800 1890272

Other Countries:

+31 13 5835404

APAC

Shanghai:

+ 86 21 2412 1618/19

Sydney:

+61 2 9751 8500



Vores kraftfulde portefølje af mærker:

CADDY ERICO HOFFMAN ILSCO SCHROFF TRACHTE

