

# Cable to Cable, Cathodic

## Data Solutions



nVent ERICO Cadweld Cathodic Connections are the preferred method of exothermically welding cathodic protection anode leads to pipes (steel or cast iron), tanks, and other structures. Cathodic protection systems are designed to prevent galvanic corrosion along a pipeline or in various structures. nVent ERICO Cadweld Cathodic Connections use a special welding material alloy to minimize heat effect on the steel, which is especially important on thin wall and high stress pipes.

### FUNKTIONER

Forms a permanent, low resistance connection

Provides a molecular bond

nVent ERICO Cadweld Exothermic Connections are rated with the same current capacity as the conductor

Portable installation equipment with no external source of power required

Installers can be easily trained to make nVent ERICO Cadweld Exothermic Connections

Connections can be visually inspected

### SPECIFIKATIONER

Table 1/2

Katalognummer	Mold Family	Conductor 1	Conductor 1 Outer Diameter, Nominal	Conductor 2	Conductor 2 Outer Diameter, Nominal
CASST1A	SS Mold Family	#10 Solid	2.59mm	#10 Solid	2.59mm
CAPCT1H1D	PC Mold Family	#6 Concentric	4.67mm	#8 Solid	3.25mm
CASST1D	SS Mold Family	#8 Solid	3.25mm	#8 Solid	3.25mm
CAPCT1V1E	PC Mold Family	#2 Concentric	7.42mm	#8 Concentric	3.71mm
CAPCT1H1E	PC Mold Family	#6 Concentric	4.67mm	#8 Concentric	3.71mm
CASST1E	SS Mold Family	#8 Concentric	3.71mm	#8 Concentric	3.71mm
CAPCT1L1E	PC Mold Family	#4 Concentric	5.89mm	#8 Concentric	3.71mm

Katalognummer	Mold Family	Conductor 1	Conductor 1 Outer Diameter, Nominal	Conductor 2	Conductor 2 Outer Diameter, Nominal
CASST1G	SS Mold Family	#6 Solid	4.11mm	#6 Solid	4.11mm
CAPCT1G1G	PT Mold Family	#6 Solid	4.11mm	#6 Solid	4.11mm
CAPCP2G1G	PC Mold Family	2/0 Concentric	10.62mm	#6 Solid	4.11mm
CAPCT1V1G	PC Mold Family	#2 Concentric	7.42mm	#6 Solid	4.11mm
CAPCT1L1H	PC Mold Family	#4 Concentric	5.89mm	#6 Concentric	4.67mm
CAPCP2C1H	PC Mold Family	1/0 Concentric	9.47mm	#6 Concentric	4.67mm
CAPCT1V1H	PC Mold Family	#2 Concentric	7.42mm	#6 Concentric	4.67mm
CAPCT1H1H	PC Mold Family	#6 Concentric	4.67mm	#6 Concentric	4.67mm
CASST1H	SS Mold Family	#6 Concentric	4.67mm	#6 Concentric	4.67mm
CASST1K	SS Mold Family	#4 Solid	5.18mm	#4 Solid	5.18mm
CASST1L	SS Mold Family	#4 Concentric	5.89mm	#4 Concentric	5.89mm
CATAN2C1L	TA Mold Family	1/0 Concentric	9.47mm	#4 Concentric	5.89mm
CATAN1V1L	TA Mold Family	#2 Concentric	7.42mm	#4 Concentric	5.89mm

Table 2/2

Katalognummer	Mold Family	Conductor 1	Conductor 1 Outer Diameter, Nominal	Conductor 2	Conductor 2 Outer Diameter, Nominal
CAPCT1L1LM	PC Mold Family	#4 Concentric	5.89mm	#4 Concentric	5.89mm
CAPCP2C1L	PC Mold Family	1/0 Concentric	9.47mm	#4 Concentric	5.89mm
CAPCT1L1L	PC Mold Family	#4 Concentric	5.89mm	#4 Concentric	5.89mm
CATAN2G1L	TA Mold Family	2/0 Concentric	10.62mm	#4 Concentric	5.89mm
CASST1V	SS Mold Family	#2 Concentric	7.42mm	#2 Concentric	7.42mm
CATAN1V1V	TA Mold Family	#2 Concentric	7.42mm	#2 Concentric	7.42mm
CATAN1Y1V	TA Mold Family	#1 Concentric	8.43mm	#2 Concentric	7.42mm
CAPCP2C1V	PC Mold Family	1/0 Concentric	9.47mm	#2 Concentric	7.42mm
CATAN2C1V	TA Mold Family	1/0 Concentric	9.47mm	#2 Concentric	7.42mm
CAPCP1V1V	PC Mold Family	#2 Concentric	7.42mm	#2 Concentric	7.42mm
CATAN2G1V	TA Mold Family	2/0 Concentric	10.62mm	#2 Concentric	7.42mm
CAPCN2G1V	PC Mold Family	2/0 Concentric	10.62mm	#2 Concentric	7.42mm
CASST1Y	SS Mold Family	#1 Concentric	8.43mm	#1 Concentric	8.43mm
CATAN2C1Y	TA Mold Family	1/0 Concentric	9.47mm	#1 Concentric	8.43mm
CATAN2C1YM	TA Mold Family	1/0 Concentric	9.47mm	#1 Concentric	8.43mm
CASSP2C	SS Mold Family	1/0 Concentric	9.47mm	1/0 Concentric	9.47mm
CATAN2C2C	TA Mold Family	1/0 Concentric	9.47mm	1/0 Concentric	9.47mm
CATAN2G2G	TA Mold Family	2/0 Concentric	10.62mm	2/0 Concentric	10.62mm

Katalognummer	Mold Family	Conductor 1	Conductor 1 Outer Diameter, Nominal	Conductor 2	Conductor 2 Outer Diameter, Nominal
CASSP2G	SS Mold Family	2/0 Concentric	10.62mm	2/0 Concentric	10.62mm

## YDERLIGERE PRODUKTOPLYSNINGER

For applications such as computer room, tunnel or other low-ventilation areas, specify a smokeless nVent ERICO Cadweld Exolon mold. Add an XL prefix to the standard mold part number when ordering (for example, a TAC2Q2Q becomes XLTAC2Q2Q). Similarly, nVent ERICO Cadweld Exolon welding material is also designated by the XL prefix (for example, 150 becomes XL150).

A gap between conductors may be required. See mold tag for more information.

Use XF19 or PLUSXF19 welding material on connections to ductile iron.

CA-XX-X-XX-XX-L-M-W		
CA	Cathodic Designation	
XX	Mold Family	
X	Price Key	
XX	Conductor Code 1	
XX	Conductor Code 2	
L*	Split Crucible	Crucible section is split on molds designed with horizontal opening for easier cleaning
M*	Mold Only	
W*	Wear Plates	Reduce mechanical abrasion of molds at cable entry points

\* Empty if none

## ADVARSEL

nVent-produkter skal kun installeres og anvendes som angivet i nVents produktvejledninger og træningsmaterialer. Vejledninger er tilgængelige på [www.nvent.com](http://www.nvent.com) og hos din nVent kundeservicerepræsentant. Forkert installation, misbrug, fejlanvendelse eller anden unkladelse af fuldt ud at følge nVents instruktioner og advarsler kan medføre funktionsfejl, materielle skader, alvorlige personskader eller død og/eller ugyldiggøre din garanti.



Vores kraftfulde portefølje af mærker:

**CADDY   ERICO   HOFFMAN   ILSCO   SCHROFF   TRACHTE**