

Laminate to Third Rail Connection Kit



FUNKTIONER

Kit includes 2000 kcmil copper laminate bond, nVent ERICO Cadweld mold allocation, batting material and two units of welding material per bond connection

Allows for thermal expansion and contraction of contact rail while maintaining current flow

Attached to the inverted bottom rail with nVent ERICO Cadweld, forming a permanent low electrical resistance connection

Laminate construction for maximum flexibility

Laminates tinned together on ends to eliminate corrosion

SPECIFIKATIONER


Table 1/2

Katalognummer	Materiale	Rail Type	Minimum Order Quantity	Conductor Size	Length (L)	Width (W)
PBK015C	Copper, Graphite, Stål	150 lb Inverted Bethlehem	25	2000 kcmil Laminate	177.8mm	31.75 mm

Table 2/2

Katalognummer	Height (H)	Angle (a)
PBK015C	31.75 mm	15 °

DIAGRAMS



ADVARSEL

nVent-produkter skal kun installeres og anvendes som angivet i nVents produktvejledninger og træningsmaterialer. Vejledninger er tilgængelige på www.nvent.com og hos din nVent kundeservicerepræsentant. Forkert installation, misbrug, fejlanvendelse eller anden undladelse af fuldt ud at følge nVents instruktioner og advarsler kan medføre funktionsfejl, materielle skader, alvorlige personskader eller død og/eller ugyldiggøre din garanti.

North America

+1.800.753.9221

Option 1 – Customer Care

Option 2 – Technical

Support

Europe

Netherlands:

+31 800-0200135

France:

+33 800 901 793

Europe

Germany:

800 1890272

Other Countries:

+31 13 5835404

APAC

Shanghai:

+ 86 21 2412 1618/19

Sydney:

+61 2 9751 8500



Vores kraftfulde portefølje af mærker:

CADDY

ERICO

HOFFMAN

ILSCO

SCHROFF

TRACHTE