

# BS-400A Four Pole Insulating Support



## CERTIFICERINGER



## FUNKTIONER

Create custom four pole distribution blocks for an electrical distribution system

Protection screen can be attached directly to the support

Includes screws to mount threaded copper busbars

Easily clips onto DIN rail or mounts to panel with screws

Halogen free

RoHS compliant

## SPECIFIKATIONER

Table 1/3

| Katalognummer | Artikelnummer | Materiale                              | Finish            | Max Working Voltage, IEC (Ui) | Working Temperature | Typical Application Current Rating |
|---------------|---------------|--|-------------------|-------------------------------|---------------------|------------------------------------|
| BS-400A       | 551250        | Stål, Glass Fibre Reinforced Polyamide | Electrogalvanized | 1000, 1500                    | -40 to 130 °C       | 160 - 630 A                        |

Table 2/3

| Katalognummer | Artikelnummer | Complies With   | Flammability Rating | Busbar Width | Busbar Thickness | Dybde (D) |
|---------------|---------------|---|---------------------|--------------|------------------|-----------|
| BS-400A       | 551250        | IEC® 60439.1,<br>IEC® 61439.1,<br>IEC® 60695-2-11 (Glow Wire Test 960 °C) | UL® 94V-0           | 15 - 32 mm   | 5 - 10 mm        | 128mm     |


Table 3/3

| Katalognummer | Artikelnummer | Height (H) | Width (W) | A      | Screw Diameter (Sc) | Unit Weight |
|---------------|---------------|------------|-----------|--------|---------------------|-------------|
| BS-400A       | 551250        | 230 mm     | 34 mm     | 123 mm | 6                   | 0.22 kg     |

## YDERLIGERE PRODUKTOPLYSNINGER

Must be used with copper busbars.

## DIAGRAMS



## ADVARSEL

nVent-produkter skal kun installeres og anvendes som angivet i nVents produktvejledninger og træningsmaterialer. Vejledninger er tilgængelige på [www.nvent.com](http://www.nvent.com) og hos din nVent kundeservicerepræsentant. Forkert installation, misbrug, fejlanvendelse eller anden undladelse af fuldt ud at følge nVents instruktioner og advarsler kan medføre funktionsfejl, materielle skader, alvorlige personskader eller død og/eller ugyldiggøre din garanti.

**North America**

+1.800.753.9221

Option 1 – Customer Care

Option 2 – Technical

Support

**Europe**

Netherlands:

+31 800-0200135

France:

+33 800 901 793

**Europe**

Germany:

800 1890272

Other Countries:

+31 13 5835404

**APAC**

Shanghai:

+ 86 21 2412 1618/19

Sydney:

+61 2 9751 8500



Vores kraftfulde portefølje af mærker:

**CADDY**

**ERICO**

**HOFFMAN**

**ILSCO**

**SCHROFF**

**TRACHTE**