

# FBS Flat Busbar Support



## CERTIFICERINGER



## FUNKTIONER

Support for threaded busbars

Three phase with neutral circuit

Plastic positioning pin for bar location

Adjusts quickly to accommodate multiple busbar widths

Protection screen can be fixed using spacers

A ground can be mounted on either side

Halogen free

## SPECIFIKATIONER

Table 1/4

Katalognummer	Artikelnummer	Materiale	Finish	Max Working Voltage, IEC (Ui)	Working Temperature	Typical Application Current Rating
FBS400A	551350	Stål, Glass Fibre Reinforced Polyamide, Aluminium	Electrogalvanized	1000, 1500	-40 to 130 °C	160 - 400 A

Table 2/4

Katalognummer	Artikelnummer	Complies With	Flammability Rating	Busbar Width	Busbar Thickness	Height (H)
FBS400A	551350	IEC® 61439.1, IEC® 60695-2-11 (Glow Wire Test 960 °C)	UL® 94V-0	15 mm, 20 mm, 32 mm	5 mm	34 mm


Table 3/4

Katalognummer	Artikelnummer	Width (W)	A	B	C	D
FBS400A	551350	465 mm	450 mm	300 mm	18 mm	26 mm

Table 4/4

Katalognummer	Artikelnummer	E	X	Unit Weight
FBS400A	551350	50 mm	6 x 8 mm	0.3 kg

## DIAGRAMS



## ADVARSEL

nVent-produkter skal kun installeres og anvendes som angivet i nVents produktvejledninger og træningsmaterialer. Vejledninger er tilgængelige på [www.nvent.com](http://www.nvent.com) og hos din nVent kundeservicerepræsentant. Forkert installation, misbrug, fejlanvendelse eller anden undladelse af fuldt ud at følge nVents instruktioner og advarsler kan medføre funktionsfejl, materielle skader, alvorlige personskader eller død og/eller ugyldiggøre din garanti.

### North America

+1.800.753.9221  
Option 1 – Customer Care  
Option 2 – Technical  
Support

### Europe

Netherlands:  
+31 800-0200135  
France:  
+33 800 901 793

### Europe

Germany:  
800 1890272  
Other Countries:  
+31 13 5835404

### APAC

Shanghai:  
+ 86 21 2412 1618/19  
Sydney:  
+61 2 9751 8500



Vores kraftfulde portefølje af mærker:

**CADDY ERICO HOFFMAN ILSCO SCHROFF TRACHTE**