

FRCB Flat Braid in Coil, Plain Copper



CERTIFICERINGER



FUNKTIONER

Braids in coil are mainly used for power distribution or earthing applications

Non-magnetic material

SPECIFIKATIONER

Materiale: Copper

Table 1/2

Katalognummer	Artikelnummer	Nominal Current	Cross Section	Number of Wires	Wire Diameter	Length
FRCB15-35	557080	200A	35mm ²	1980	0.15mm	25m
FRCB15-100	557150	360A	100mm ²	5664	0.15mm	25m
FRCB15-75	557130	300A	75mm ²	4256	0.15mm	25m
FRCB15-50	557100	250A	50mm ²	2848	0.15mm	25m
FRCB15-25	557060	150A	25mm ²	1404	0.15mm	25m
FRCB15-10	557030	75A	10mm ²	576	0.15mm	25m
FRCB15-40	557090	220A	40mm ²	2272	0.15mm	25m

Katalognummer	Artikelnummer	Nominal Current	Cross Section	Number of Wires	Wire Diameter	Length
FRCB15-16	557040	120A	16mm ²	896	0.15mm	25m

Table 2/2

Katalognummer	Artikelnummer	Thickness	Width	Unit Weight
FRCB15-35	557080	2.5 mm	23 mm	0.35 kg
FRCB15-100	557150	4 mm	40 mm	1 kg
FRCB15-75	557130	4 mm	30 mm	0.75 kg
FRCB15-50	557100	3 mm	28 mm	0.5 kg
FRCB15-25	557060	1.5 mm	23 mm	0.25 kg
FRCB15-10	557030	1.5 mm	10 mm	0.1 kg
FRCB15-40	557090	2.5 mm	25 mm	0.4 kg
FRCB15-16	557040	1.5 mm	15 mm	0.16 kg

YDERLIGERE PRODUKTOPLYSNINGER

Unit weight is per meter (3.28').

ADVARSEL

nVent-produkter skal kun installeres og anvendes som angivet i nVents produktvejledninger og træningsmaterialer. Vejledninger er tilgængelige på www.nvent.com og hos din nVent kundeservicerepræsentant. Forkert installation, misbrug, fejlanvendelse eller anden unladelse af fuldt ud at følge nVents instruktioner og advarsler kan medføre funktionsfejl, materielle skader, alvorlige personskader eller død og/eller ugyldiggøre din garanti.

North America

+1.800.753.9221
Option 1 – Customer Care
Option 2 – Technical
Support

Europe

Netherlands:
+31 800-0200135
France:
+33 800 901 793

Europe

Germany:
800 1890272
Other Countries:
+31 13 5835404

APAC

Shanghai:
+ 86 21 2412 1618/19
Sydney:
+61 2 9751 8500



Vores kraftfulde portefølje af mærker:

CADDY ERICO HOFFMAN ILSCO SCHROFF TRACHTE