


## Barrieresæt, monteret på beslag



Divides wireway into two or three compartments. Plated spring steel brackets hold barriers in place by friction fit inside wireway. Order barrier and bracket separately. Recommended spacing increments of 3 ft.

### FUNKTIONER

---

Divides wireway into two or three compartments

Plated spring steel brackets hold barriers in place by friction fit inside wireway

Order barrier and bracket separately. Recommended spacing increments of 3 feet

## SPECIFIKATIONER

<b>Farvekode:</b>	ANSI 61
<b>Finish:</b>	Galvaniseret; Struktur Pulvermaling
<b>Farve:</b>	Gray
<b>Materiale:</b>	Lakeret Stål

Table 1/1

Katalognummer	Type	Højde	Bredde	Dybde	Tykkelse
F66BB2C	Barrier Kit	152mm	152mm	25mm	1.9mm
F44BB2C	Barrier Kit	102mm	102mm	25mm	1.9mm
F66BB3C	Barrier Kit	152mm	152mm		1.9mm
F66B560	Barrier Kit	152mm	152mm	3048mm	1.9mm
F44BB3C	Barrier Kit	102mm	102mm		1.9mm
F44B360	Barrier Kit	102mm	102mm	1524mm	1.9mm

## YDERLIGERE PRODUKTOPLYSNINGER

Sealing Plates package consists of five barriers or five brackets. Each barrier is 60 inches long.

## ADVARSEL

nVent-produkter skal kun installeres og anvendes som angivet i nVents produktvejledninger og træningsmaterialer. Vejledninger er tilgængelige på [www.nvent.com](http://www.nvent.com) og hos din nVent kundeservicerepræsentant. Forkert installation, misbrug, fejlanvendelse eller anden undladelse af fuldt ud at følge nVents instruktioner og advarsler kan medføre funktionsfejl, materielle skader, alvorlige personskader eller død og/eller ugyldiggøre din garanti.



Vores kraftfulde portefølje af mærker:

**CADDY ERICO HOFFMAN ILSCO SCHROFF TRACHTE**