


Plug-in busbar | Stromverteilung, MSBS



This plug-in busbar, MSBS, can withstand a rated current up to 1400A, and has been tested according to IEC 61439. It is a flexible, easy to mount solution.

MERKMALE

Beschreibung: Vertical busbar to build up the plug-in system. The MSBS bars are fixed in the MSVH supports with standard bolts, washers and nuts. The rated current can be increased up to 2 x 1400A if the incoming connection is in the middle.

Material: Tin plated aluminium.

Lieferumfang: 4 pieces of busbars.

SPEZIFIKATIONEN

Table 1/1

Katalognummer	Höhe	Breite	Tiefe	Gehäusematerial	Produktfamilie	Material
MSBS41418	1800mm	40mm	82mm	Baustahl	Freistehend	Aluminium
MSBS41420	2000mm	40mm	82mm	Baustahl	Freistehend	Aluminium
MSBS41422	2200mm	40mm	82mm	Baustahl	Freistehend	Aluminium

ZUSÄTZLICHE PRODUKTDDETAILS

*In: Rated current. *Icw: Rated short-time withstand current.

WARNUNG

nVent-Produkte müssen in Übereinstimmung mit den Produktinformationsblättern und dem Schulungsmaterial von nVent installiert und verwendet werden. Informationsblätter sind verfügbar unter www.nVent.com sowie bei Ihrem nVent-Kundendienstvertreter. Unsachgemäße Installation, Missbrauch, Fehlanwendung oder andere Handlungen im Widerspruch zu den Anweisungen und Warnungen von nVent können zu Fehlfunktionen, Anlagenschäden, schwerer Körperverletzung sowie zum Tod führen und/oder haben die Annullierung der Garantie zur Folge.



Unser starkes markenportfolio:

CADDY ERICO HOFFMAN ILSCO SCHROFF TRACHTE