

Modulschiene, Typ R-ST, hinten, stabil, Standard, 28 TE

KATALOGNUMMER

34566-528



Combinations of horizontal rails and side panels

„+“ can be combined, „-“ combination not recommended

	Standard 1.0	Standard 1.5	Standard 2.0	Standard 2.5
Standard 1.0	-	+	+	+
Standard 1.5	+	+	+	+
Standard 2.0	+	+	-	-
Standard 2.5	+	+	-	-
Standard 3.0				
Standard 3.5				
Standard 4.0				
Standard 4.5				
Standard 5.0				
Standard 5.5				
Standard 6.0				
Standard 6.5				
Standard 7.0				
Standard 7.5				
Standard 8.0				
Standard 8.5				
Standard 9.0				
Standard 9.5				
Standard 10.0				
Standard 10.5				
Standard 11.0				
Standard 11.5				
Standard 12.0				
Standard 12.5				
Standard 13.0				
Standard 13.5				
Standard 14.0				
Standard 14.5				
Standard 15.0				
Standard 15.5				
Standard 16.0				
Standard 16.5				
Standard 17.0				
Standard 17.5				
Standard 18.0				
Standard 18.5				
Standard 19.0				
Standard 19.5				
Standard 20.0				
Standard 20.5				
Standard 21.0				
Standard 21.5				
Standard 22.0				
Standard 22.5				
Standard 23.0				
Standard 23.5				
Standard 24.0				
Standard 24.5				
Standard 25.0				
Standard 25.5				
Standard 26.0				
Standard 26.5				
Standard 27.0				
Standard 27.5				
Standard 28.0				
Standard 28.5				
Standard 29.0				
Standard 29.5				
Standard 30.0				
Standard 30.5				
Standard 31.0				
Standard 31.5				
Standard 32.0				
Standard 32.5				
Standard 33.0				
Standard 33.5				
Standard 34.0				
Standard 34.5				
Standard 35.0				
Standard 35.5				
Standard 36.0				
Standard 36.5				
Standard 37.0				
Standard 37.5				
Standard 38.0				
Standard 38.5				
Standard 39.0				
Standard 39.5				
Standard 40.0				
Standard 40.5				
Standard 41.0				
Standard 41.5				
Standard 42.0				
Standard 42.5				
Standard 43.0				
Standard 43.5				
Standard 44.0				
Standard 44.5				
Standard 45.0				
Standard 45.5				
Standard 46.0				
Standard 46.5				
Standard 47.0				
Standard 47.5				
Standard 48.0				
Standard 48.5				
Standard 49.0				
Standard 49.5				
Standard 50.0				
Standard 50.5				
Standard 51.0				
Standard 51.5				
Standard 52.0				
Standard 52.5				
Standard 53.0				
Standard 53.5				
Standard 54.0				
Standard 54.5				
Standard 55.0				
Standard 55.5				
Standard 56.0				
Standard 56.5				
Standard 57.0				
Standard 57.5				
Standard 58.0				
Standard 58.5				
Standard 59.0				
Standard 59.5				
Standard 60.0				
Standard 60.5				
Standard 61.0				
Standard 61.5				
Standard 62.0				
Standard 62.5				
Standard 63.0				
Standard 63.5				
Standard 64.0				
Standard 64.5				
Standard 65.0				
Standard 65.5				
Standard 66.0				
Standard 66.5				
Standard 67.0				
Standard 67.5				
Standard 68.0				
Standard 68.5				
Standard 69.0				
Standard 69.5				
Standard 70.0				
Standard 70.5				
Standard 71.0				
Standard 71.5				
Standard 72.0				
Standard 72.5				
Standard 73.0				
Standard 73.5				
Standard 74.0				
Standard 74.5				
Standard 75.0				
Standard 75.5				
Standard 76.0				
Standard 76.5				
Standard 77.0				
Standard 77.5				
Standard 78.0				
Standard 78.5				
Standard 79.0				
Standard 79.5				
Standard 80.0				
Standard 80.5				
Standard 81.0				
Standard 81.5				
Standard 82.0				
Standard 82.5				
Standard 83.0				
Standard 83.5				
Standard 84.0				
Standard 84.5				
Standard 85.0				
Standard 85.5				
Standard 86.0				
Standard 86.5				
Standard 87.0				
Standard 87.5				
Standard 88.0				
Standard 88.5				
Standard 89.0				
Standard 89.5				
Standard 90.0				
Standard 90.5				
Standard 91.0				
Standard 91.5				
Standard 92.0				
Standard 92.5				
Standard 93.0				
Standard 93.5				
Standard 94.0				
Standard 94.5				
Standard 95.0				
Standard 95.5				
Standard 96.0				
Standard 96.5				
Standard 97.0				
Standard 97.5				
Standard 98.0				
Standard 98.5				
Standard 99.0				
Standard 99.5				
Standard 100.0				

Die Modulschiene vom Typ Rugged ST, ermöglicht die isolierte Montage einer Backplane. Die Isolierung erfolgt durch einen Isolierstreifen.

ZERTIFIZIERUNGEN



MERKMALE

Typ R-ST „Rugged“ Modulschiene mit 3-Loch-Befestigung zur Erhöhung der Stabilität

Aluminiumprofil, Oberfläche eloxiert, Kontaktfläche leitfähig, ohne TE-Bedruckung

TE-Bedruckung erfolgt erst ab 28 TE

PRODUKTMERKMALE

Breite Gestell: 28HP

Anzahl Verpackungen: 1

Oberfläche: Eloxiert

Länge: 147.32mm

Material: Aluminium

Produktfamilie: EuropacPRO

Produkttyp: Modulschiene

Typ: Robust, ST

Passt zu: Baugruppenträger

Net Weight: 0.07kg

ZUSÄTZLICHE PRODUKTDDETAILS

Bitte beachten Sie, dass Lieferungen nur in den jeweils angegebenen LLG (Lieferlosgrößen), LLG z. B. 5 Stück, 10 Stück, 50 Stück usw.) möglich sind. Davon abweichende Bestellmengen (z. B. 2 Stück) werden auf die nächst mögliche lieferbare Menge = Lieferlosgröße (LLG) abgeändert.

WARNUNG

nVent-Produkte müssen in Übereinstimmung mit den Produktinformationsblättern und dem Schulungsmaterial von nVent installiert und verwendet werden. Informationsblätter sind verfügbar unter www.nVent.com sowie bei Ihrem nVent-Kundendienstvertreter. Unsachgemäße Installation, Missbrauch, Fehlanwendung oder andere Handlungen im Widerspruch zu den Anweisungen und Warnungen von nVent können zu Fehlfunktionen, Anlagenschäden, schwerer Körperverletzung sowie zum Tod führen und/oder haben die Annullierung der Garantie zur Folge.

North America

All locations
+1.763.422.2661
Chat with us:
nvent.com/schroff

Europe

Straubenhardt, Germany
+49.7082.794.0
Betschdorf, France
+33.3.88.90.64.90
Warsaw, Poland
+48.22.209.98.35
Assago, Italy
+39.02.932.7141
Chat with us:
nvent.com/schroff

Asia

Shanghai, China
+86.21.2412.6943
Qingdao, China
+86.532.8771.6101
Singapore
+65.6768.5800
Shin-Yokohama, Japan
+81.45.476.0271
Chat with us:
nvent.com/schroff

Middle East & India

Dubai, United Arab Emirates
+971.4.378.1700
Bangalore, India
+91.80.6715.2001
Istanbul, Turkey
+90.216.250.7374
Chat with us:
nvent.com/schroff



Unser starkes markenportfolio:

CADDY ERICO HOFFMAN ILSCO SCHROFF TRACHTE