# Varistar CP Cabinet Frame, 47 U, 2200H, 600W, 1200D

## Data Solutions

### CATALOG NUMBER

**20630-116**




| W | D | Xf | Xr | C |
|---|---|---|---|---|
| 600 | 600 | 50 | 50 | 500 |
| 600 | 800 | 50 | 50 | 700 |
| 600 | 900 | 50 | 50 | 800 |
| 600 | 1000 | 50 | 50 | 900 |
| 600 | 1100 | 50 | 50 | 1000 |
| 600 | 1200 | 50 | 50 | 1100 |





Varistar CP welded frame is available for static load requirements and can be integrated with 19", ETSI or mounting plate. Additionally, castors can be added to the frame if needed.

However, if you require castors for your application, you might want to consider a mobile frame that already includes castors.

### FEATURES

| |
|---|
| Welded, finish powder-coated, black gray, RAL 7021 |
| St, 1.5 mm, zinc-plated, with central GND/grounding point |
| Static load-carrying capacity max. 1600 kg |
| Please order adjustable feet separately |

## PRODUCT ATTRIBUTES

- Rack Height: 47U
- Height: 2200mm
- Width: 600mm
- Depth: 1200mm
- Package Quantity: 1
- Color: Black Grey
- Color Code: RAL 7021
- Complies With: IEC 61587-1; IEC 61587-3
- Frame Material: Steel
- Material: Steel
- Product Family: Varistar CP
- Product Type: Cabinet/Rack Frame
- Static Load: 1600kg
- Type: Standard
- Works With: Varistar CP
- Net Weight: 42.66kg

## ADDITIONAL PRODUCT DETAILS

Castor can be added to the frame. If you will need a castor for your application, you can order a mobile frame which include castors.

## WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

Our powerful portfolio of brands:

CADDY ERICO HOFFMAN ILSCO SCHROFF TRACHTE

©2026 nVent. All nVent marks and logos are owned or licensed by nVent Services GmbH or its affiliates. All other trademarks are the property of their respective owners. nVent reserves the right to change specifications without notice.

This document is system-generated.