

# Conductor Saddle



## FEATURES

Secures lightning protection conductors and prevents displacement

Mechanically secured with Pozidriv screws or nails

Fix using countersunk M6 screw and wall plug

## SPECIFICATIONS

**Material:** Leaded Gunmetal

Table 1/2


Catalog Number	Conductor Size	Complies With	Length (L)	Thread Length (TL)	Width (W)	Height (H)
CCS095	95 mm <sup>2</sup> Stranded	IEC® 62561-4	55mm	12mm	20 mm	19.5 mm
CCS070	70 mm <sup>2</sup> Stranded	IEC® 62561-4	55mm	12mm	20 mm	18.5 mm
CCS050	50 mm <sup>2</sup> Stranded	IEC® 62561-4	55mm	12mm	20 mm	17.5 mm

Table 2/2

Catalog Number	Hole Size (HS)	Thread Size (TS)	Unit Weight
CCS095	6.6 mm	M6	0.1 kg
CCS070	6.6 mm	M6	0.1 kg
CCS050	6.6 mm	M6	0.1 kg

## DIAGRAMS

---



## WARNING

---

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at [www.nvent.com](http://www.nvent.com) and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

### North America

+1.800.753.9221  
Option 1 – Customer Care  
Option 2 – Technical  
Support

### Europe

Netherlands:  
+31 800-0200135  
France:  
+33 800 901 793

### Europe

Germany:  
800 1890272  
Other Countries:  
+31 13 5835404

### APAC

Shanghai:  
+ 86 21 2412 1618/19  
Sydney:  
+61 2 9751 8500



Our powerful portfolio of brands:

**CADDY ERICO HOFFMAN ILSCO SCHROFF TRACHTE**