

Horizontal Rail, Rear, Type R-ST, Rugged, Standard, 28 HP

CATALOG NUMBER

34566-528



Combinations of horizontal rails and side panels

		"A" can be combined	"C" combination not recommended	
RAILWAY 18		-		not recommended
RAILWAY 22		+		not recommended
RAILWAY 25		not recommended		not recommended
RAILWAY 28		+		+
RAILWAY 32		+		+
RAILWAY 35		+		+
RAILWAY 38		+		+
RAILWAY 42		+		+
RAILWAY 45		+		+
RAILWAY 48		+		+
RAILWAY 52		+		+
RAILWAY 55		+		+
RAILWAY 58		+		+
RAILWAY 62		+		+
RAILWAY 65		+		+
RAILWAY 68		+		+
RAILWAY 72		+		+
RAILWAY 75		+		+
RAILWAY 78		+		+
RAILWAY 82		+		+
RAILWAY 85		+		+
RAILWAY 88		+		+
RAILWAY 92		+		+

Side panel

RAILWAY 18

RAILWAY 22

RAILWAY 25

RAILWAY 28

RAILWAY 32

RAILWAY 35

RAILWAY 38

RAILWAY 42

RAILWAY 45

RAILWAY 48

RAILWAY 52

RAILWAY 55

RAILWAY 58

RAILWAY 62

RAILWAY 65

RAILWAY 68

RAILWAY 72

RAILWAY 75

RAILWAY 78

RAILWAY 82

RAILWAY 85

RAILWAY 88

RAILWAY 92

The horizontal rail, type rugged ST enable the isolated assembly of a backplane. The isolation is done by an insulation strip.

CERTIFICATIONS



FEATURES

Type R-ST "rugged" horizontal rail with 3-hole fixing for increased robustness

Aluminum extrusion, anodized finish, conductive contact surface, with HP markings

With HP units printed from 28 HP upwards

PRODUCT ATTRIBUTES

Rack Width: 28HP

Package Quantity: 1

Finish: Anodized

Length: 147.32mm

Material: Aluminum

Product Family: EuropacPRO

Product Type: Horizontal Rail

Type: Rugged, ST

Works With: Subracks

Net Weight: 0.07kg

ADDITIONAL PRODUCT DETAILS

Please take into consideration that deliveries may be carried out in the stated SPQs (SPQ, e.g. 5 pieces, 10 pieces, 50 pieces, etc.). Differing order quantities (e.g. 2 pieces) may be changed to the next possible delivery quantity = Standard Pack Quantity.

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

North America

All locations
+1.763.422.2661
Chat with us:
nvent.com/schroff

Europe

Straubenhardt, Germany
+49.7082.794.0
Betschdorf, France
+33.3.88.90.64.90
Warsaw, Poland
+48.22.209.98.35
Assago, Italy
+39.02.932.7141
Chat with us:
nvent.com/schroff

Asia

Shanghai, China
+86.21.2412.6943
Qingdao, China
+86.532.8771.6101
Singapore
+65.6768.5800
Shin-Yokohama, Japan
+81.45.476.0271
Chat with us:
nvent.com/schroff

Middle East & India

Dubai, United Arab
Emirates
+971.4.378.1700
Bangalore, India
+91.80.6715.2001
Istanbul, Turkey
+90.216.250.7374
Chat with us:
nvent.com/schroff



Our powerful portfolio of brands:

CADDY ERICO HOFFMAN ILSCO SCHROFF TRACHTE