

Universal Conductor Support Block



FEATURES

Provides elevated support for lightning conductors

SPECIFICATIONS

Material: Polyethylene;Nylon


Table 1/2

Catalog Number	Article Number	Conductor Size	Tape Size	Concrete Filled	Depth (D)	Height (H)
SFTBE	106060	6 mm Solid - 11 mm Solid	25 x 3 mm, 26 x 2 mm, 30 x 2 mm, 30 x 6 mm Max	No	138mm	80 mm
SFTBC	106080	6 mm Solid - 11 mm Solid	25 x 3 mm, 26 x 2 mm, 30 x 2 mm, 30 x 6 mm Max	Yes	138mm	80 mm

Table 2/2

Catalog Number	Article Number	Width (W)	Unit Weight
SFTBE	106060	138 mm	0.1 kg
SFTBC	106080	138 mm	0.98 kg

DIAGRAMS



WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

North America

+1.800.753.9221
Option 1 – Customer Care
Option 2 – Technical
Support

Europe

Netherlands:
+31 800-0200135
France:
+33 800 901 793

Europe

Germany:
800 1890272
Other Countries:
+31 13 5835404

APAC

Shanghai:
+ 86 21 2412 1618/19
Sydney:
+61 2 9751 8500



Our powerful portfolio of brands:

CADDY ERICO HOFFMAN ILSCO SCHROFF TRACHTE