We connect and protect

Socket Strip With 2 Supply Cable, 3 Phase, IEC

Data Solutions

CATALOG NUMBER

60110-287

Modular, compact PDU with two power cord inputs that can be connected to an A and B power feed. Space saving design in one chassis.

CERTIFICATIONS

RoHS COMPLIANT

EAC

FEATURES

- Horizontal and vertical assembly possible
- Two connector cables (halved in direction of length), 3 m (with open end), 2 x 3 phase, 400 VAC (red, black, white area)
- Socket strips can be rotated in all directions (in 90° increments) during installation
- Mounting height 1 U

PRODUCT ATTRIBUTES

- Socket Type: IEC C13
- Socket Quantity: 48
- Switched Outlets: No
- Voltage AC: 400V
- Package Quantity: 1

Color: Grey; Black; Red

Depth: 44mm

Finish: Anodized

Height: 44mm

Length: 1848.5mm

Material: Aluminum; Polyamide

Product Type: Socket Strip

Net Weight: 4.2kg

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

Our powerful portfolio of brands:

CADDY ERICO HOFFMAN ILSCO SCHROFF TRACHTE

©2026 nVent. All nVent marks and logos are owned or licensed by nVent Services GmbH or its affiliates. All other trademarks are the property of their respective owners. nVent reserves the right to change specifications without notice.

This document is system-generated.