

# Four Hole Flat Bracket



## FEATURES

Used to create metal frames with nVent CADDY Eristrut channels

## SPECIFICATIONS

Table 1/2

Catalog Number	Article Number	Material	Finish	A	Hole Size (HS)	Thickness (T)
ZEA104	387540	Steel	Hot-Dip Galvanized	168 mm	14	6
ZE104	313040	Steel	Hot-Dip Galvanized	168 mm	14	6
ZEA104S6	387542	Stainless Steel 316 (EN 1.4401)		168 mm	14	6

Table 2/2

Catalog Number	Article Number	Screw Included	Screw Diameter (Sc)	Screw Length (L)
ZEA104	387540	No		
ZE104	313040	Yes	10	25mm
ZEA104S6	387542	No		

## DIAGRAMS

---



## WARNING

---

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at [www.nvent.com](http://www.nvent.com) and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

### North America

+1.800.753.9221

Option 1 – Customer Care

Option 2 – Technical

Support

### Europe

Netherlands:

+31 800-0200135

France:

+33 800 901 793

### Europe

Germany:

800 1890272

Other Countries:

+31 13 5835404

### APAC

Shanghai:

+ 86 21 2412 1618/19

Sydney:

+61 2 9751 8500



Our powerful portfolio of brands:

**CADDY**

**ERICO**

**HOFFMAN**

**ILSCO**

**SCHROFF**

**TRACHTE**

