

# Plinth Combining Profiles, PCP



This profile acts as a stabiliser and allows cables to be routed between bayed enclosures, creating the ideal solution when cables have to be installed underneath the enclosure.

## FEATURES

---

Description: Acts as a stabiliser when cabling is routed between bayed enclosures. With the PCP, plinths can be combined and fixed to the floor before the enclosures are mounted on them. The PCP can be used when cables have to go under the enclosure. For 200 mm high plinths, the PCP can be mounted in three different heights, top, middle or bottom. The hole pattern for cage nuts and M5 x 10 screws, allows accessories to be mounted.

Material: 2 mm steel plate.

Finish: RAL 7022 structured powder coating.

Pack quantity: 2 profiles with mounting accessories.

## SPECIFICATIONS

---

**Thickness:** 2mm  
**Material:** Mild Steel  
**Finish:** Powder Coated  
**Color Code:** RAL 7022  
**Color:** Umbra Gray

Table 1/1

Catalog Number	Height	Width	Depth	Enclosure Material	Product Family
PCP05	60mm	62mm	500mm	Mild Steel	Free-Standing
PCP10	60mm	61mm	1000mm	Mild Steel	Free-Standing
PCP06	60mm	62mm	600mm	Mild Steel	Free-Standing
PCP04	60mm	62mm	400mm	Mild Steel	Free-Standing
PCP08	60mm	62mm	800mm	Mild Steel	Free-Standing

## WARNING

---

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at [www.nvent.com](http://www.nvent.com) and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.



Our powerful portfolio of brands:

**CADDY ERICO HOFFMAN ILSCO SCHROFF TRACHTE**