

Socket Strip, IEC C13, Metered

Data Solutions

PDU with local power meter. Relevant Power data are shown on an integrated display.



CERTIFICATIONS



FEATURES

Socket strips can be rotated through all four directions (in 90° increments) during installation

Mounting height 1 U

Integrated measurement and display via local display unit

Socket strips with IEC 60320-C13 sockets

Horizontal and vertical mounting

SPECIFICATIONS

Table 1/2

Catalog Number	Product Type	Socket Type	Socket Quantity	Color	Switched Outlets	Length
60110-296	Socket Strip	IEC C13	8	Grey	Yes	438.5mm

Table 2/2

Catalog Number	Voltage AC	Depth	Material	Package Quantity
----------------	------------	-------	----------	------------------

60110-296	230V	44mm	Aluminum, Polyamide	1
-----------	------	------	---------------------	---

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.



Our powerful portfolio of brands:

CADDY ERICO HOFFMAN ILSCO SCHROFF TRACHTE