

FPN Universal Anchor



FEATURES

Expansion fixing for wood or drywall / plasterboard screws

For use in concrete, brick and lightweight concrete

SPECIFICATIONS

Static Load Safety Factor: 5:1

Material: Nylon

Table 1/2

Catalog Number	Article Number	Screw Diameter	Length	Drill Bit Diameter	Drill Hole Depth	Static Load 1
FPN10	570730	6 - 8 mm	50mm	10mm	60mm	1500N
FPN12	570740	8 - 10 mm	60mm	12mm	70mm	1800N

Table 2/2

Catalog Number	Article Number	Static Load 2	Static Load 3
FPN10	570730	850N	800N
FPN12	570740	950N	800N

ADDITIONAL PRODUCT DETAILS

Refer to Static Load 1 when anchoring in non-cracked concrete C20/25. Refer to Static Load 2 when anchoring in solid brick Mz 20. Refer to Static Load 3 when anchoring in solid sand-lime brick KS 20.

Static loads are calculated using the maximum Screw Diameter.

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

North America

+1.800.753.9221

Option 1 – Customer Care

Option 2 – Technical

Support

Europe

Netherlands:

+31 800-0200135

France:

+33 800 901 793

Europe

Germany:

800 1890272

Other Countries:

+31 13 5835404

APAC

Shanghai:

+ 86 21 2412 1618/19

Sydney:

+61 2 9751 8500



Our powerful portfolio of brands:

CADDY

ERICO

HOFFMAN

ILSCO

SCHROFF

TRACHTE

