


150M Standard U-Bolt



FEATURES

Pipe support for general piping applications

Comes complete with 4 nuts (2 installed on each end)

Conforms with Federal Specification WW-H-171 (Type 24), Manufacturers Standardization Society ANSI®/MSS-SP-58 (Type 24)

SPECIFICATIONS

Finish: Electrogalvanized


Material: Steel

Table 1/1

Catalog Number	Outer Diameter (OD)	Screw Length (L)	A	B	Static Load
150M0100EG	33.4 mm	60.5mm	93.7 mm	39.8 mm	1930N
150M0125EG	42.2 mm	60.5mm	104.8 mm	51.7 mm	4800N
150M0200EG	60.3 mm	63.5mm	122.38 mm	69.9 mm	4800N
150M0150EG	48.3 mm	63.5mm	109.6 mm	57.8 mm	4800N
150M0300EG	88.9 mm	76.2mm	160.3 mm	101.6 mm	8900N
150M0250EG	73 mm	76.2mm	146.1 mm	85.7 mm	8900N
150M0400EG	114.3 mm	76.2mm	185.7 mm	127 mm	8950N
150M0500EG	141.3 mm	76.2mm	211.1 mm	154 mm	8950N
150M0600EG	168.3 mm	95.3mm	257.1 mm	184.2 mm	14350N
150M0800EG	219.1 mm	95.3mm	308 mm	235 mm	14350N

Catalog Number	Outer Diameter (OD)	Screw Length (L)	A	B	Static Load
150M1000EG	273.1 mm	101.6mm	369.8 mm	292.1 mm	21450N
150M1200EG	323.9 mm	108mm	430.1 mm	346.1 mm	29900N

DIAGRAMS



WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

North America

+1.800.753.9221
Option 1 – Customer Care
Option 2 – Technical Support

Europe

Netherlands:
+31 800-0200135
France:
+33 800 901 793

Europe

Germany:
800 1890272
Other Countries:
+31 13 5835404

APAC

Shanghai:
+ 86 21 2412 1618/19
Sydney:
+61 2 9751 8500



Our powerful portfolio of brands:

CADDY ERICO HOFFMAN ILSCO SCHROFF TRACHTE

