

Clevis Bolt Spacer

Data Solutions



FEATURES

Seismically braces the 401 Clevis Hanger series for lateral load

Retrofit ability allows the spacer to be installed after the clevis and pipe are installed

Ears easily pinch closed around the clevis hanger cross bolt with pliers

FM® Specification Tested (up to 8" Pipe Size)

SPECIFICATIONS

Finish: Electrogalvanized


Material: Steel

Table 1/1

Catalog Number	Width (W)	Height (H)	Thickness (T)	Depth (D)
CSBCS0200	57.9mm	13mm	1.9mm	13mm
CSBCS1000	267.2mm	31mm	1.9mm	27.7mm
CSBCS0500	139.7mm	24.9mm	1.9mm	22.9mm
CSBCS0150	43.4mm	13mm	1.9mm	13mm
CSBCS0250	70.6mm	17mm	1.9mm	16.5mm
CSBCS0100	30.7mm	13mm	1.9mm	13mm
CSBCS0800	217.4mm	31mm	1.9mm	27.7mm
CSBCS0300	86.6mm	17mm	1.9mm	16.5mm

Catalog Number	Width (W)	Height (H)	Thickness (T)	Depth (D)
CSBCS0400	112mm	17mm	1.9mm	16.5mm
CSBCS1200	318mm	31mm	1.9mm	27.7mm
CSBCS0125	39.4mm	13mm	1.9mm	13mm
CSBCS0600	166.6mm	24.9mm	1.9mm	22.9mm
CSBCS0350	99.3mm	17mm	1.9mm	16.5mm

DIAGRAMS



WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.



Our powerful portfolio of brands:

CADDY ERICO HOFFMAN ILSCO SCHROFF TRACHTE