

## Interlock bars, FMB



This connection bar mechanically connects a system actuator with the secondary door interlocking kit, and allows the secondary door to be opened only when the primary door is opened first.

### FEATURES

---

Description: For MCF/MCS enclosures. Interlock rods mechanically link all secondary doors to the primary door. Rod length corresponds to enclosure door width.

Material: Zinc plated steel.

Pack quantity: 5 pieces with mounting material.

## SPECIFICATIONS

---

**Thickness:** 3mm  
**Material:** Mild Steel  
**Finish:** Zinc Plated

Table 1/1

Catalog Number	Article Number	Height	Width	Depth	Enclosure Material	Product Family
FMB1000	FMB1000	17mm	860mm	17mm	Mild Steel	Free-Standing
FMB800	FMB800	17mm	660mm	17mm	Mild Steel	Free-Standing
FMB600	FMB600	17mm	460mm	17mm	Mild Steel	Free-Standing
FMB1200	FMB1200	17mm	1060mm	17mm	Mild Steel	Free-Standing

## WARNING

---

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at [www.nvent.com](http://www.nvent.com) and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.



Our powerful portfolio of brands:

**CADDY ERICO HOFFMAN ILSCO SCHROFF TRACHTE**