

Plug-In Unit Protection Panel

The panels protect the solder or the component side of a PCB. A coding with a separate coding strip is not possible.



CERTIFICATIONS



FEATURES

Keying/coding with separate keying/coding strip is not possible

Usable connectors in accordance with EN 60603 (DIN 41612): Construction type B, C, D, F, H, R

Stainless steel, 0.8 mm

SPECIFICATIONS

- Product Type:** Cover
- Material:** Stainless Steel


Table 1/1

| Catalog Number | Package Quantity | Works With |
|----------------|------------------|----------------|
| 20809-371 | 1 | Component Side |
| 30809-571 | 1 | Solder Side |

ADDITIONAL PRODUCT DETAILS

PCB is offset to the right by 1 HP.

DIAGRAMS



WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

North America

All locations
+1.763.422.2661
Chat with us:
nvent.com/schroff

Europe

Straubenhardt, Germany
+49.7082.794.0
Betschdorf, France
+33.3.88.90.64.90
Warsaw, Poland
+48.22.209.98.35
Assago, Italy
+39.02.932.7141
Chat with us:
nvent.com/schroff

Asia

Shanghai, China
+86.21.2412.6943
Qingdao, China
+86.532.8771.6101
Singapore
+65.6768.5800
Shin-Yokohama, Japan
+81.45.476.0271
Chat with us:
nvent.com/schroff

Middle East & India

Dubai, United Arab Emirates
+971.4.378.1700
Bangalore, India
+91.80.6715.2001
Istanbul, Turkey
+90.216.250.7374
Chat with us:
nvent.com/schroff



Our powerful portfolio of brands:

CADDY ERICO HOFFMAN ILSCO SCHROFF TRACHTE