

# Copper Shim

## Data Solutions



### FEATURES

Wrapped around the cable until the diameter is about the same as the cable opening in the mold

### SPECIFICATIONS


**Material:** Copper

Table 1/1

Catalog Number	Article Number	Length (L)	Width (W)	Thickness (T)
B140K		114.3mm	38.1mm	0.33mm
B141C		63.5mm	76.2mm	0.33mm
B141A		38.1mm	76.2mm	0.33mm
B140A		38.1mm	76.2mm	0.33mm
B140L		139.7mm	38.1mm	0.33mm
B140B		63.5mm	76.2mm	0.33mm
B140N	165610	76.2mm	38.1mm	0.33mm

## DIAGRAMS

---



## WARNING

---

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at [www.nvent.com](http://www.nvent.com) and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

⚠ WARNING: This product can expose you to chemicals including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).



Our powerful portfolio of brands:

**CADDY ERICO HOFFMAN ILSCO SCHROFF TRACHTE**