

# Flange Protector for Multi-Function C-Clamp



## FEATURES

Designed to protect paint on steel flanges

## SPECIFICATIONS

Table 1/1				
Catalog Number	Article Number	Material	Finish	Screw Diameter (Sc)
SPPM6HD	336200	Steel	Hot-Dip Galvanized	6
SPPM6S4	336220	Stainless Steel 304 (EN 1.4301)		6
SPPM8HD	336210	Steel	Hot-Dip Galvanized	8
SPPM8S4	336230	Stainless Steel 304 (EN 1.4301)		8


## ADDITIONAL PRODUCT DETAILS

When the laquer protective plates are used, the clamping range is reduced by approximately 3 mm and the permissible load must be reduced by 20%.

The screw tip should be placed so it will not damage the paint of the steel structure.

## DIAGRAMS

---



## WARNING

---

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at [www.nvent.com](http://www.nvent.com) and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

### North America

+1.800.753.9221

Option 1 – Customer Care

Option 2 – Technical

Support

### Europe

Netherlands:

+31 800-0200135

France:

+33 800 901 793

### Europe

Germany:

800 1890272

Other Countries:

+31 13 5835404

### APAC

Shanghai:

+ 86 21 2412 1618/19

Sydney:

+61 2 9751 8500



Our powerful portfolio of brands:

**CADDY**

**ERICO**

**HOFFMAN**

**ILSCO**

**SCHROFF**

**TRACHTE**

