



Socket Strip, IEC C13, With Wieland® Input, C13, 6 Sockets, 19", Red, With Overcurrent Protection

Data Solutions

CATALOG NUMBER

60110-351



Modular, compact PDU with many function elements. Using a 1 U by 1 U aluminum chassis the PDU can easily be integrated in a rack. The Wieland connector allows easy combination with different power input cords.

CERTIFICATIONS



FEATURES

Input via Wieland® GST 18 plug
Installation height 1 U
In accordance with IEC 60320
Horizontal or vertical mounting
Output via IEC 60320 C-13 sockets
Socket strips can be rotated through all four directions (in 90° increments) during fitting

PRODUCT ATTRIBUTES

Socket Type: IEC C13
Socket Quantity: 6
Switched Outlets: No
Voltage AC: 230V
Function: Overcurrent Protection
Package Quantity: 1
Color: Red
Depth: 44mm
Finish: Anodized
Length: 438.5mm
Material: Aluminum; Polyamide
Product Type: Socket Strip
Net Weight: 0.9kg

ADDITIONAL PRODUCT DETAILS

Please order mounting bracket for vertical mounting separately.

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.



Our powerful portfolio of brands:

CADDY ERICO HOFFMAN ILSCO SCHROFF TRACHTE