

Hangers



Hangers are used to support a wireway run. The drop hanger is normally attached to an overhead beam or ceiling while the bracket hanger can be used for wall, floor or ceiling installations. Hangers are finished with paint over plated surfaces.

FEATURES

Hangers are used to support a wireway run

The drop hanger is normally attached to an overhead beam or ceiling while the bracket hanger can be used for wall, floor or ceiling installations

Hangers are finished with paint over plated surfaces

SPECIFICATIONS

Color Code: ANSI 61
Finish: Galvanized; Powder Coated
Color: Gray
Material: Mild Steel

Table 1/1

| Catalog Number | Article Number | Type | Height | Width | Thickness | Sealing Plate Type |
|----------------|----------------|--------|--------|-------|-----------|--------------------|
| F88HD | 14990 | Hanger | 203mm | 203mm | 1.9mm | None |
| F66HD | 14590 | Hanger | 152mm | 152mm | 1.9mm | None |
| F44HD | 14380 | Hanger | 102mm | 102mm | 1.9mm | None |
| F22HD | 14170 | Hanger | 64mm | 64mm | 1.9mm | None |
| F88HB | 15000 | Hanger | 203mm | 203mm | 1.9mm | |
| F66HB | 14600 | Hanger | 152mm | 152mm | 1.9mm | |
| F44HB | 14390 | Hanger | 102mm | 102mm | 1.9mm | |
| F22HB | 14180 | Hanger | 64mm | 64mm | 1.9mm | |

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.



Our powerful portfolio of brands:

CADDY ERICO HOFFMAN ILSCO SCHROFF TRACHTE