


# Insertor/Extractor Handle Type IET, Black Lever, Grey Button, Bottom; 10 pieces

## CATALOG NUMBER

**20817-652**



The inserter/extractor handle, type IET in accordance with IEEE 1101.10. Two of these handles can overcome a single lever force of 700 N (per pair).

## CERTIFICATIONS



## FEATURES

Suitable for insertion and extraction forces up to 700 N (per pair)

In accordance with IEEE 1101.10 and IEC 60297-3-102

A microswitch can be mounted

|                                              |
|----------------------------------------------|
| Package Quantity: 10                         |
| Handle Type: IET; Bottom Front; Top Rear I/O |
| Flammability Rating: UL® 94V-0               |
| Color: Jet Black                             |
| Color Code: RAL 9005                         |
| Complies With: EN 45545-2                    |
| Depth (D): 39.15mm                           |
| Height (H): 44.65mm                          |
| Material: Polycarbonate; Zinc Alloy          |
| Product Type: Handle                         |
| Type: Inserter/Extractor, Standard           |
| Width (W): 19.8mm                            |
| Works With: Front Panels                     |
| Net Weight: 0.233kg                          |

Please order Coding pegs and Microswitch separately.

Technical drawing of a door handle assembly, showing exploded view, top view, and bottom view with dimensions.

**Exploded View:** Shows the handle assembly with a dimension of 4.07.

**Top View:** Shows the handle assembly with dimensions: 20, 2.54, 2.54, 7.62, 0.7, 12.75, 2.5, 22.75, 2.5, 3.8, 8.52, 10.15, 26, 2.5, 3.6, 6.1, 14, 4.5.

**Bottom View:** Shows the handle assembly with dimensions: 20, 2.54, 2.54, 7.62, 4, 2.54, 7.62.

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at [www.nvent.com](http://www.nvent.com) and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause

product malfunction, property damage, serious bodily injury and death and/or void your warranty.

**North America**

All locations  
+1.763.422.2661  
Chat with us:  
[nvent.com/schroff](https://nvent.com/schroff)

**Europe**

Straubenhardt, Germany  
+49.7082.794.0  
Betschdorf, France  
+33.3.88.90.64.90  
Warsaw, Poland  
+48.22.209.98.35  
Assago, Italy  
+39.02.932.7141  
Chat with us:  
[nvent.com/schroff](https://nvent.com/schroff)

**Asia**

Shanghai, China  
+86.21.2412.6943  
Qingdao, China  
+86.532.8771.6101  
Singapore  
+65.6768.5800  
Shin-Yokohama, Japan  
+81.45.476.0271  
Chat with us:  
[nvent.com/schroff](https://nvent.com/schroff)

**Middle East & India**

Dubai, United Arab Emirates  
+971.4.378.1700  
Bangalore, India  
+91.80.6715.2001  
Istanbul, Turkey  
+90.216.250.7374  
Chat with us:  
[nvent.com/schroff](https://nvent.com/schroff)



Our powerful portfolio of brands:

**CADDY   ERICO   HOFFMAN   ILSCO   SCHROFF   TRACHTE**