

Industrial Stack Base with Stud, Horizontal/Vertical Cable Run



FEATURES

Cast air terminal base for use with horizontal and/or vertical conductor runs

Welded threaded stud for use with expansion anchors

SPECIFICATIONS

Material: Bronze
Conductor Size, UL: Class 2 (4/0 Max)

Table 1/2

Catalog Number	Finish	Thread Size 1 (TS1)	Thread Size 2 (TS2)	Thread Length (TL)	Depth (D)	Height (H)
LPC436LG	Bare	5/8" UNC	1/2" UNC	38.1mm	25.4mm	152.4 mm
LPC436SH	Bare	5/8" UNC	1/2" UNC	22.22mm	25.4mm	152.4 mm
LPLC436SH	Lead Covered	5/8" UNC	1/2" UNC	22.22mm	25.4mm	152.4 mm
LPLC436LG	Lead Covered	5/8" UNC	1/2" UNC	38.1mm	25.4mm	152.4 mm

Table 2/2


Catalog Number	Width (W)	Unit Weight
LPC436LG	76.2 mm	0.73 kg
LPC436SH	76.2 mm	0.73 kg
LPLC436SH	76.2 mm	1.9 kg

Catalog Number	Width (W)	Unit Weight
LPLC436LG	76.2 mm	1.9 kg

ADDITIONAL PRODUCT DETAILS

Where applicable, lead covering thickness is a minimum of 1/16" (1.59 mm) and is not included in the stated dimensions.

DIAGRAMS



WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

North America

+1.800.753.9221
Option 1 – Customer Care
Option 2 – Technical
Support

Europe

Netherlands:
+31 800-0200135
France:
+33 800 901 793

Europe

Germany:
800 1890272
Other Countries:
+31 13 5835404

APAC

Shanghai:
+ 86 21 2412 1618/19
Sydney:
+61 2 9751 8500



Our powerful portfolio of brands:

CADDY ERICO HOFFMAN ILSCO SCHROFF TRACHTE