

VMEbus J2 Backplane



The nVent SCHROFF VMEbus Backplanes have outstanding high-frequency noise suppression and very high MTBF values due to ceramic capacitors and SMD fabrication technology.

CERTIFICATIONS



FEATURES

In accordance with ANSI/VITA 1-1994 VME64 standard

3 U with J2 plane

Connection or isolation between the digital GND and chassis GND can be changed via screw

Termination passive

Supply voltages can be provided via powerbugs (ring tag M4) or FASTONs

Multiple backplanes can be placed side by side without loss of slot space

SPECIFICATIONS

Table 1/2

| Catalog Number | Product Type | Number of Slots | Rack Height | Backplane Type | System Slot | Slot Width |
|----------------|--------------|-----------------|-------------|----------------|-------------|------------|
| 23001-051 | Backplane | 21 | 3U | VMEbus, J2 | Slot 1 Left | 4HP |
| 23001-046 | Backplane | 16 | 3U | VMEbus, J2 | Slot 1 Left | 4HP |
| 23001-040 | Backplane | 10 | 3U | VMEbus, J2 | Slot 1 Left | 4HP |
| 23001-036 | Backplane | 6 | 3U | VMEbus, J2 | Slot 1 Left | 4HP |
| 23001-035 | Backplane | 5 | 3U | VMEbus, J2 | Slot 1 Left | 4HP |

| Catalog Number | Product Type | Number of Slots | Rack Height | Backplane Type | System Slot | Slot Width |
|----------------|--------------|-----------------|-------------|----------------|-------------|------------|
| 23001-034 | Backplane | 4 | 3U | VMEbus, J2 | Slot 1 Left | 4HP |
| 23001-033 | Backplane | 3 | 3U | VMEbus, J2 | Slot 1 Left | 4HP |
| 23001-032 | Backplane | 2 | 3U | VMEbus, J2 | Slot 1 Left | 4HP |

Table 2/2

| Catalog Number | Connector Type | Power Connector Type | Height | Width | Package Quantity |
|----------------|----------------|------------------------------|---------|---------|------------------|
| 23001-051 | DIN 41612, C96 | Power Bugs for M4 Cable Lugs | 128.5mm | 425.3mm | 1 |
| 23001-046 | DIN 41612, C96 | Power Bugs for M4 Cable Lugs | 128.5mm | 321.3mm | 1 |
| 23001-040 | DIN 41612, C96 | Power Bugs for M4 Cable Lugs | 128.5mm | 199.2mm | 1 |
| 23001-036 | DIN 41612, C96 | Power Bugs for M4 Cable Lugs | 128.5mm | 120.5mm | 1 |
| 23001-035 | DIN 41612, C96 | Power Bugs for M4 Cable Lugs | 128.5mm | 100.2mm | 1 |
| 23001-034 | DIN 41612, C96 | Power Bugs for M4 Cable Lugs | 128.5mm | 79.8mm | 1 |
| 23001-033 | DIN 41612, C96 | Power Bugs for M4 Cable Lugs | 128.5mm | 59.7mm | 1 |
| 23001-032 | DIN 41612, C96 | Power Bugs for M4 Cable Lugs | 128.5mm | 40.4mm | 1 |

ADDITIONAL PRODUCT DETAILS

Other configurations available on request.

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

North America

All locations

+1.763.422.2661

Chat with us:

nvent.com/schroff

Europe

Straubenhardt, Germany

+49.7082.794.0

Betschdorf, France

+33.3.88.90.64.90

Warsaw, Poland

+48.22.209.98.35

Assago, Italy

+39.02.932.7141

Chat with us:

nvent.com/schroff

Asia

Shanghai, China

+86.21.2412.6943

Qingdao, China

+86.532.8771.6101

Singapore

+65.6768.5800

Shin-Yokohama, Japan

+81.45.476.0271

Chat with us:

nvent.com/schroff

Middle East & India

Dubai, United Arab Emirates

+971.4.378.1700

Bangalore, India

+91.80.6715.2001

Istanbul, Turkey

+90.216.250.7374

Chat with us:

nvent.com/schroff



Our powerful portfolio of brands:

CADDY

ERICO

HOFFMAN

ILSCO

SCHROFF

TRACHTE