

Hammer Die

Data Solutions



FEATURES

Hardened steel die

Used to form the end of a field-made bond

Formed end designed to fit specific nVent ERICO Cadweld mold

SPECIFICATIONS

Material: Steel

Table 1/2

| Catalog Number | Article Number | Type | Conductor Size | nVent ERICO Sleeve |
|----------------|----------------|-----------|-----------------------------|--------------------|
| WD80 | | Power | 1/0 Concentric | S05F |
| JD05 | | Grounding | 1/0 Concentric | S05F |
| WD84 | | Power | 2/0 Concentric, 1/0 Ropelay | S03F |
| JD03 | | Grounding | 2/0 Concentric | S03F |
| WD85 | | Power | 2/0 Ropelay | S06F |
| JD06 | | Grounding | 2/0 Ropelay | S06F |
| SBD50 | | Signal | 3/16" Bondstrand | SBS12C |
| JD01 | | Grounding | 4/0 Concentric | S01F |

| Catalog Number | Article Number | Type | Conductor Size | nVent ERICO Sleeve |
|----------------|----------------|-----------|--|--------------------|
| WD82 | | Power | 95 mm ² Concentric, 4/0 Concentric | S01F |
| WD83 | | Power | 4/0 Ropelay | S02F |
| JD02 | | Grounding | 4/0 Ropelay | S02F |
| WD88 | | Power | 4/0 Welding cable | S429F3N16 |
| SBD51 | | Signal | 5/16" Bondstrand | SBS09C |
| WD94 | | Power | 35 mm ² Concentric | S17F |
| SBD55 | | Signal | 35 mm ² Concentric | S17F |
| PBWD102 | 184200 | Power | 120 mm ² Concentric | H106F |
| PBWD104 | | Power | 145 mm ² Concentric | S429F3N16 |
| WD87 | | Power | 150 mm ² Ropelay | S24F |
| WD105 | | Power | 240 mm ² Concentric | S429FY922 |
| PBWD106 | 184090 | Power | 240 mm ² Concentric | S429FY922 |

Table 2/2

| Catalog Number | Article Number | Type | Conductor Size | nVent ERICO Sleeve |
|----------------|----------------|-----------|-----------------------------|--------------------|
| PBWD99 | | Power | 240 mm ² Ropelay | S429F3N16 |
| JD07 | | Grounding | 250 kcmil Ropelay | S07F |
| WD79 | | Power | 500 kcmil Ropelay | S429F3S20 |
| JD09 | | Grounding | #2 Concentric | S09F |
| JD11 | | Grounding | #4 Concentric | S20F |

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.



Our powerful portfolio of brands:

CADDY ERICO HOFFMAN ILSCO SCHROFF TRACHTE