

# Double Cable Holder with Plug



## FEATURES

Easy-to-open latch allows cables to be added or removed quickly after installation

Tool-free push-in installation after hole has been drilled into the concrete

Plastic conduit clips can be attached to the holder allowing the support of cables and conduits using a single hole in the concrete

Halogen free

UV-stabilized

## SPECIFICATIONS

Table 1/2


Catalog Number	Article Number	Material	Temperature	Cable Capacity	Diameter (Ø)	Drill Hole Diameter
SCSH50	800044	Polypropylene	-10 to 85 °C	80	10 mm	6mm

Table 2/2

Catalog Number	Article Number	Drill Hole Depth	A	B	Static Load
SCSH50	800044	30mm	108 mm	96 mm	200N

## DIAGRAMS

---



## WARNING

---

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at [www.nvent.com](http://www.nvent.com) and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

### North America

+1.800.753.9221  
Option 1 – Customer Care  
Option 2 – Technical  
Support

### Europe

Netherlands:  
+31 800-0200135  
France:  
+33 800 901 793

### Europe

Germany:  
800 1890272  
Other Countries:  
+31 13 5835404

### APAC

Shanghai:  
+ 86 21 2412 1618/19  
Sydney:  
+61 2 9751 8500



Our powerful portfolio of brands:

**CADDY ERICO HOFFMAN ILSCO SCHROFF TRACHTE**

