


PropacPRO Rear Panel, Full Width, Unshielded

The rear panel, full width for PropacPRO Case mounts to the frame of the case. With or without vented slots.



CERTIFICATIONS



FEATURES

Alu panel, 2.0 mm (84 HP 2.5 mm)

Mounting with support bracket on case (right and left)

SPECIFICATIONS

| | |
|------------------------|------------|
| Material: | Aluminum |
| Finish: | Anodized |
| Works With: | Cases |
| Product Family: | PropacPRO |
| Type: | Rear Panel |
| Product Type: | Side Panel |

Table 1/2

| Catalog Number | Rack Height | Rack Width | Design Feature | Package Quantity |
|----------------|-------------|------------|----------------|------------------|
| 24576-153 | 4U | 63HP | Perforated | 1 |
| 24576-145 | 2U | 63HP | Perforated | 1 |
| 24576-050 | 3U | 84HP | Non-Perforated | 1 |
| 24576-149 | 3U | 63HP | Perforated | 1 |
| 24576-150 | 3U | 84HP | Perforated | 1 |

| Catalog Number | Rack Height | Rack Width | Design Feature | Package Quantity |
|----------------|-------------|------------|----------------|------------------|
| 24576-049 | 3U | 63HP | Non-Perforated | 1 |
| 24576-052 | 4U | 42HP | Non-Perforated | 1 |
| 24576-148 | 3U | 42HP | Perforated | 1 |
| 24576-045 | 2U | 63HP | Non-Perforated | 1 |
| 24576-152 | 4U | 42HP | Perforated | 1 |
| 24576-053 | 4U | 63HP | Non-Perforated | 1 |
| 24576-047 | 3U | 28HP | Non-Perforated | 1 |
| 24576-054 | 4U | 84HP | Non-Perforated | 1 |
| 24576-048 | 3U | 42HP | Non-Perforated | 1 |
| 24576-154 | 4U | 84HP | Perforated | 1 |
| 24576-146 | 2U | 84HP | Perforated | 1 |
| 24576-044 | 2U | 42HP | Non-Perforated | 1 |
| 24576-046 | 2U | 84HP | Non-Perforated | 1 |
| 24576-158 | 6U | 84HP | Perforated | 1 |
| 24576-147 | 3U | 28HP | Perforated | 1 |

Table 2/2

| Catalog Number | Rack Height | Rack Width | Design Feature | Package Quantity |
|----------------|-------------|------------|----------------|------------------|
| 24576-058 | 6U | 84HP | Non-Perforated | 1 |
| 24576-144 | 2U | 42HP | Perforated | 1 |

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

North America

All locations

+1.763.422.2661

Chat with us:

nvent.com/schroff

Europe

Straubenhardt, Germany

+49.7082.794.0

Betschdorf, France

+33.3.88.90.64.90

Warsaw, Poland

+48.22.209.98.35

Assago, Italy

+39.02.932.7141

Chat with us:

nvent.com/schroff

Asia

Shanghai, China

+86.21.2412.6943

Qingdao, China

+86.532.8771.6101

Singapore

+65.6768.5800

Shin-Yokohama, Japan

+81.45.476.0271

Chat with us:

nvent.com/schroff

Middle East & India

Dubai, United Arab

Emirates

+971.4.378.1700

Bangalore, India

+91.80.6715.2001

Istanbul, Turkey

+90.216.250.7374

Chat with us:

nvent.com/schroff



Our powerful portfolio of brands:

CADDY

ERICO

HOFFMAN

ILSCO

SCHROFF

TRACHTE