

# Cross Fitting Lay-in Hinged-Cover



Lay-in Hinged-Cover Cross Fittings are used for routing cables in four directions in wireway runs. Used when there are four branches, all open along the same side.

## INDUSTRY STANDARDS

---

Certified by Canadian Standards Association

## FEATURES

---

Lay-in Hinged-Cover Cross Fittings are used for routing cables in four directions in wireway runs

Used when there are four branches, all open along the same side

## SPECIFICATIONS

---

**Color Code:** ANSI 61  
**Finish:** Galvanized; Powder Coated  
**Color:** Gray  
**Material:** Mild Steel

Table 1/1

Catalog Number	Article Number	Type	Height	Width	Thickness
F88LC	19310	Cross Fitting	203mm	203mm	1.9mm
F66LC	18660	Cross Fitting	152mm	152mm	1.9mm
F44LC	18420	Cross Fitting	102mm	102mm	1.9mm
F126LC	18860	Cross Fitting	305mm	152mm	1.9mm
F22LC	18190	Cross Fitting	64mm	64mm	1.9mm

## ADDITIONAL PRODUCT DETAILS

---

Each sealing plate also includes one gasket and one set of screws to join sections.

## WARNING

---

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at [www.nvent.com](http://www.nvent.com) and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.



Our powerful portfolio of brands:

**CADDY ERICO HOFFMAN ILSCO SCHROFF TRACHTE**