

# TDS130 Replacement Module



## CERTIFICATIONS



## FEATURES


Replacement module for TDS130 Series

## SPECIFICATIONS

Catalog Number	TDS130M150
Article Number	702432
Nominal System Voltage (Un)	120 - 150 VAC
Max Continuous Operating Voltage (Uc)	170 VAC
Voltage Protection Rating (VPR)	800 V @ 3 kA L-N 500 V @ 3 kA L+N-PE
Nominal Discharge Current (In)	8kA 8/20 $\mu$ s
Max Discharge Current (Imax), L-N	20kA 8/20 $\mu$ s
Max Discharge Current (Imax), L-PE	20kA 8/20 $\mu$ s
Frequency	0 - 100 Hz
Enclosure Material	UL® 94V-0 Thermoplastic
Temperature	-40 to 80 °C

<b>Catalog Number</b>	<b>TDS130M150</b>
Module Width	1 M
Depth (D)	49mm
Height (H)	45 mm
Width (W)	18 mm
Unit Weight	0.07 kg

## DIAGRAMS



## WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at [www.nvent.com](http://www.nvent.com) and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

### North America

+1.800.753.9221  
Option 1 – Customer Care  
Option 2 – Technical  
Support

### Europe

Netherlands:  
+31 800-0200135  
France:  
+33 800 901 793

### Europe

Germany:  
800 1890272  
Other Countries:  
+31 13 5835404

### APAC

Shanghai:  
+ 86 21 2412 1618/19  
Sydney:  
+61 2 9751 8500



Our powerful portfolio of brands:

**CADDY ERICO HOFFMAN ILSCO SCHROFF TRACHTE**