

Industrial Stack Base with Stud, Horizontal Cable Run



CERTIFICATIONS



FEATURES

Cast air terminal base for use with horizontal conductor runs

Welded threaded stud for use with expansion anchors

SPECIFICATIONS

Material: Brass
Conductor Size, UL: Class 2 (4/0 Max)

Table 1/2

| Catalog Number | Finish | Thread Size 1 (TS1) | Thread Size 2 (TS2) | Thread Length (TL) | Depth (D) | Height (H) |
|----------------|--------------|---------------------|---------------------|--------------------|-----------|------------|
| LPC435SH | Bare | 5/8" UNC | 1/2" UNC | 22.22mm | 25.4mm | 100 mm |
| LPC435LG | Bare | 5/8" UNC | 1/2" UNC | 38.1mm | 25.4mm | 100 mm |
| LPLC435SH | Lead Covered | 5/8" UNC | 1/2" UNC | 22.22mm | 25.4mm | 100 mm |
| LPLC435LG | Lead Covered | 5/8" UNC | 1/2" UNC | 38.1mm | 25.4mm | 100 mm |

Table 2/2

| Catalog Number | Width (W) | Unit Weight | Certifications |
|----------------|-----------|-------------|---|
| LPC435SH | 76.2 mm | 0.54 kg | E202878-Combined_CoC, E202878-Combined_CoC |
| LPC435LG | 76.2 mm | 0.54 kg | E202878-Combined_CoC, E202878-Combined_CoC |
| LPLC435SH | 76.2 mm | 1.21 kg | |
| LPLC435LG | 76.2 mm | 1.21 kg | |

ADDITIONAL PRODUCT DETAILS

Where applicable, lead covering thickness is a minimum of 1/16" (1.59 mm) and is not included in the stated dimensions.

DIAGRAMS



WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

North America

+1.800.753.9221
Option 1 – Customer Care
Option 2 – Technical
Support

Europe

Netherlands:
+31 800-0200135
France:
+33 800 901 793

Europe

Germany:
800 1890272
Other Countries:
+31 13 5835404

APAC

Shanghai:
+ 86 21 2412 1618/19
Sydney:
+61 2 9751 8500



Our powerful portfolio of brands:

CADDY ERICO HOFFMAN ILSCO SCHROFF TRACHTE