


Seismic Rubber Mount



The Vibration Isolation Mount line from nVent CADDY is used to minimize vibrations produced by supported systems such as mechanical equipment, pumps, ductwork, piping, and in-line, exhaust and cabinet fans.

FEATURES

- Used to support HVAC equipment, air conditioning units, compressors, pumps, motors and fans pumps
- Used when resistance to wind or seismic forces is required
- Powder coated steel housing
- Elements are color coded for accurate selection and easy field verification
- Steel cups provide uniform loading
- Built-in leveling device allows for fine-tuning adjustment

SPECIFICATIONS

Table 1/1					
Catalog Number	Article Number	Length	Width	Height	Ultimate Static Load
CSBSRM100	801432	76.2mm	152.4mm	117.48mm	445N
CSBSRM550	801435	76.2mm	152.4mm	117.48mm	2447N
CSBSRM200	801433	76.2mm	152.4mm	117.48mm	890N
CSBSRM350	801434	76.2mm	152.4mm	117.48mm	1557N

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

North America

+1.800.753.9221

Option 1 – Customer Care

Option 2 – Technical

Support

Europe

Netherlands:

+31 800-0200135

France:

+33 800 901 793

Europe

Germany:

800 1890272

Other Countries:

+31 13 5835404

APAC

Shanghai:

+ 86 21 2412 1618/19

Sydney:

+61 2 9751 8500



Our powerful portfolio of brands:

CADDY ERICO HOFFMAN ILSCO SCHROFF TRACHTE

