


# Grounding/Grounding Busbar Kit for Ring Terminations

## Data Solutions



Copper strip typically housed inside switchgear, panel boards, and busway enclosures for grounding. They are also used to connect high voltage equipment at electrical switchyards, and low voltage equipment in battery banks.

### FEATURES

To screw on grounding cables with ring tabs

Threaded fixing points M5 in intervals of 20 mm

Assembly insulated from the frame

Maximum current capacity 200 A

Connection 35 mm<sup>2</sup> with a clamp (accessory 21120-209)

### SPECIFICATIONS

**Product Type:** Grounding Kit

Table 1/1

Catalog Number	Length	Material	Package Quantity	Type
20118-860	440mm	Copper	1	Ring Termination
20118-864	1980mm	Copper	1	Ring Termination
20118-861	980mm	Copper	1	Ring Termination
20118-863	1900mm	Copper	1	Ring Termination
20118-862	1680mm	Copper	1	Ring Termination

## WARNING

---

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at [www.nvent.com](http://www.nvent.com) and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.



Our powerful portfolio of brands:

**CADDY ERICO HOFFMAN ILSCO SCHROFF TRACHTE**