

Ground Mounted Plinth, PGM



Cables can be easily routed through the ground plinth, which is mounted underground, allowing cables to be channelled and therefore, wired more quickly.

FEATURES

Description: Ground mounted plinth 1000 mm height. Excavation depth: 700-950 mm.

Material: 2 mm galvanized steel.

Finish: RAL 7035 polyester powder coated.

Pack quantity: 1 kit of ground mounted plinth.

SPECIFICATIONS

Thickness: 2mm
Finish: Galvanized
Material: Galvanized Steel
Color: Light Gray
Color Code: RAL 7035

Table 1/1

| Catalog Number | Height | Width | Depth | Enclosure Material | Product Family |
|----------------|--------|--------|-------|--------------------|----------------|
| PGM10086 | 1000mm | 800mm | 600mm | Aluminum | Free-Standing |
| PGM10066 | 1000mm | 600mm | 600mm | Aluminum | Free-Standing |
| PGM10126 | 1000mm | 1200mm | 600mm | Aluminum | Free-Standing |
| PGM10184 | 1000mm | 1800mm | 400mm | Aluminum | Free-Standing |
| PGM10124 | 1000mm | 1200mm | 400mm | Aluminum | Free-Standing |
| PGM10084 | 1000mm | 800mm | 400mm | Aluminum | Free-Standing |
| PGM10064 | 1000mm | 600mm | 400mm | Aluminum | Free-Standing |

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.



Our powerful portfolio of brands:

CADDY ERICO HOFFMAN ILSCO SCHROFF TRACHTE