

Conductor Sleeve

Data Solutions



FEATURES

Used to adapt a limited range of smaller size cables to a larger size nVent ERICO Cadweld Mold

Provides strength and stability on finely-stranded copper conductors


SPECIFICATIONS

Material: Copper

Table 1/1

Catalog Number	Article Number	Finish	Type	Length (L)	Thickness (T)	Diameter (Ø)
S429F2N16		Tinned	Flared	25.4mm	0.51mm	13.72mm
PBS24F		Tinned	Flared	38.1mm	0.79mm	20.19mm
S05F		Tinned	Flared	25.4mm	0.79mm	9.93mm
B1331K		Tinned	Straight	25.4mm	0.79mm	3.56mm
S17F		Tinned	Flared	25.4mm	0.79mm	8.74mm
H105	180230		Straight	23.5mm	1mm	3mm
H102	180170		Straight	25mm	1.05mm	4.3mm
H103	180180		Straight	25mm	1.2mm	5.3mm

DIAGRAMS



WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.



Our powerful portfolio of brands:

CADDY ERICO HOFFMAN ILSCO SCHROFF TRACHTE