We connect and protect

nVent ERIFLEX FleXbus IP66 Upgrade Kit, 105 mm Max dia, 0.05 kg

Data Solutions

CATALOG NUMBER

FLEXCEIP66C100

CERTIFICATIONS

UKCA

FEATURES

- Upgrades IP55 to IP66 by adding the heat shrink tubing
- Increases the dustproof and waterproof level
- Halogen free

PRODUCT ATTRIBUTES

- Article Number: 508145
- Forming Temperature: 135°C min
- Shrink Ratio: 4:1
- Working Temperature: −55 to 130°C
- Height: 10cm

Unit Weight: 0.05kg

ADDITIONAL PRODUCT DETAILS

FLEXCEIP66C50 Upgrade Kit is suitable for the following FleXbus Conductor’s cross section: 220, 360, 545 and 640 mm2.

FLEXCEIP66C100 Upgrade Kit is suitable for the following FleXbus Conductor’s cross section: 960, 1280 and 1810 mm2.

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

Our powerful portfolio of brands:

CADDY ERICO HOFFMAN ILSCO SCHROFF TRACHTE

©2026 nVent. All nVent marks and logos are owned or licensed by nVent Services GmbH or its affiliates. All other trademarks are the property of their respective owners. nVent reserves the right to change specifications without notice.

This document is system-generated.