

Mounting Frame, UMF



Modular components can be pre-mounted and the frame can be adjusted to the desired depth to hold large equipment, for example.

FEATURES

Description: For easy mounting of DIN-rail components. The DIN-rails are adjustable in height.

Material: Galvanized steel.

Delivery: Vertical profiles, reinforced DIN-rails, supporting brackets and mounting accessories.

Adjustable DIN rail frame for compact polyester wall mounted enclosures

Modular components can be pre-mounted onto the chassis before being fitted into the enclosure

The frame allows the components to be mounted and adjusted to the correct depth

The frame allows panel builders to quickly install modular components or large equipment as the frame can be adjusted in depth

SPECIFICATIONS

Finish: Galvanized
Material: Galvanized Steel

Table 1/1

| Catalog Number | Height | Width | Module Quantity | DIN Rail | Enclosure Material |
|----------------|--------|-------|-----------------|----------|--------------------|
| UMF6403 | 615mm | 415mm | 54 | 3 | Polyester |
| UMF4302 | 415mm | 315mm | 24 | 3 | Polyester |
| UMF3202 | 315mm | 215mm | 12 | 3 | Polyester |
| UMF5403 | 515mm | 415mm | 54 | 3 | Polyester |
| UMF7503 | 735mm | 535mm | 88 | 4 | Polyester |
| UMF8604 | 835mm | 635mm | 96 | 4 | Polyester |
| UMF10805 | 1035mm | 835mm | 180 | 5 | Polyester |

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.



Our powerful portfolio of brands:

CADDY ERICO HOFFMAN ILSCO SCHROFF TRACHTE