

19" Distribution Box

Distribution box is used to house PDUs which safely distribute electricity from power source to devices in a circuit.



CERTIFICATIONS



FEATURES

For installation of power distribution modules on DIN profile rails (DIN 43880)

Two neutral conductors for terminal clamps from 4 ... 35 mm²

With cable support rail at rear, strain relief with clamps

SPECIFICATIONS

Table 1/1

| Catalog Number | Product Type | Package Quantity | Finish | Material | Packaging |
|----------------|-------------------|------------------|----------------------|----------|-----------|
| 60118-434 | Power Distributor | 1 | Aluminum-Zinc Plated | Steel | |
| 60118-521 | Power Distributor | 1 | Aluminum-Zinc Plated | Steel | Overseas |

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

North America

All locations
+1.763.422.2661
Chat with us:
nvent.com/schroff

Europe

Straubenhardt, Germany
+49.7082.794.0
Betschdorf, France
+33.3.88.90.64.90
Warsaw, Poland
+48.22.209.98.35
Assago, Italy
+39.02.932.7141
Chat with us:
nvent.com/schroff

Asia

Shanghai, China
+86.21.2412.6943
Qingdao, China
+86.532.8771.6101
Singapore
+65.6768.5800
Shin-Yokohama, Japan
+81.45.476.0271
Chat with us:
nvent.com/schroff

Middle East & India

Dubai, United Arab Emirates
+971.4.378.1700
Bangalore, India
+91.80.6715.2001
Istanbul, Turkey
+90.216.250.7374
Chat with us:
nvent.com/schroff



Our powerful portfolio of brands:

CADDY ERICO HOFFMAN ILSCO SCHROFF TRACHTE