We connect and protect

Fibre Optic Cable Ducting

Data Solutions



Cable spool to be assembled in a rack to manage fiber optic cables.

CERTIFICATIONS

RoHS COMPLIANT

FEATURES

- For secure, damage-free laying of optic fiber cables
- For assembly on 19" panel/slide mount
- Cable ducting, radius 30 mm, width 50 mm, side panel height 15 mm
- Mounted from inside or outside on panel/slide mount

SPECIFICATIONS

Table 1/1

Catalog Number	Works With	Material	Color	Finish
23130-391	Varistar CP	Steel	Black	Powder Coated

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause

product malfunction, property damage, serious bodily injury and death and/or void your warranty.

Our powerful portfolio of brands:

CADDY ERICO HOFFMAN ILSCO SCHROFF TRACHTE

©2026 nVent. All nVent marks and logos are owned or licensed by nVent Services GmbH or its affiliates. All other trademarks are the property of their respective owners. nVent reserves the right to change specifications without notice.

This document is system-generated.