

Outside Cable Fixing Bars, CABP



This adjustable cable bar provides a safe way of securing cables underneath the enclosure, which optimises the space inside it. External strains are avoided, protecting the installed equipment from damage.

FEATURES

Description: Suspended below the bottom plates

Material: 2 mm zinc plated steel.

Pack quantity: 2 bars with mounting accessories. For 1200 mm wide, 4 bars with mounting accessories.

Mounting requirements: Add CAC clamps depending on diameter of cable.

SPECIFICATIONS

Thickness: 2mm
Material: Mild Steel
Finish: Zinc Plated

Table 1/1

| Catalog Number | Article Number | Height | Width | Depth | Enclosure Material | Product Family |
|----------------|----------------|--------|--------|-------|--------------------|----------------|
| CABP800 | CABP800 | 45mm | 800mm | 36mm | Mild Steel | |
| CABP1000 | CABP1000 | 45mm | 1000mm | 36mm | Mild Steel | |
| CABP1200 | CABP1200 | 45mm | 1200mm | 36mm | Mild Steel | |
| CABP600 | CABP600 | 45mm | 600mm | 36mm | Mild Steel | |
| CABP500 | CABP500 | 45mm | 500mm | 36mm | Mild Steel | |
| CABP400 | CABP400 | 45mm | 400mm | 36mm | Mild Steel | Free-Standing |

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.



Our powerful portfolio of brands:

CADDY ERICO HOFFMAN ILSCO SCHROFF TRACHTE