


Inpac Perforated Rail for Mounting of DIN Connectors EN 60603-2, DIN 41612, 75 HP

CATALOG NUMBER

20828-131



Perforated flat rail for connector mounting EN 60603-2 and DIN 41612, suitable for Inpac.

FEATURES

For Connector Mounting According to DIN 41612

PRODUCT ATTRIBUTES

Product Type: Perforated Rail

Product Family: Inpac

Works With: Cases

Rack Width: 75HP

Package Quantity: 2

Finish: Passivated

Material: Aluminum

Net Weight: 0.074kg

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

North America

All locations
+1.763.422.2661
Chat with us:
nvent.com/schroff

Europe

Straubenhardt, Germany
+49.7082.794.0
Betschdorf, France
+33.3.88.90.64.90
Warsaw, Poland
+48.22.209.98.35
Assago, Italy
+39.02.932.7141
Chat with us:
nvent.com/schroff

Asia

Shanghai, China
+86.21.2412.6943
Qingdao, China
+86.532.8771.6101
Singapore
+65.6768.5800
Shin-Yokohama, Japan
+81.45.476.0271
Chat with us:
nvent.com/schroff

Middle East & India

Dubai, United Arab
Emirates
+971.4.378.1700
Bangalore, India
+91.80.6715.2001
Istanbul, Turkey
+90.216.250.7374
Chat with us:
nvent.com/schroff



Our powerful portfolio of brands:

CADDY ERICO HOFFMAN ILSCO SCHROFF TRACHTE