

Four Hole Flat Bracket



FEATURES

Used to create metal frames with nVent CADDY Eristrut channels

SPECIFICATIONS


Table 1/2

Catalog Number	Article Number	E-Number	Material	Finish	A	Hole Size (HS)
ZEA104	387540	3535426	Steel	Hot-Dip Galvanized	168 mm	14
ZE104	313040	1340571	Steel	Hot-Dip Galvanized	168 mm	14
ZEA104S6	387542		Stainless Steel 316 (EN 1.4401)		168 mm	14

Table 2/2

Catalog Number	Article Number	E-Number	Thickness (T)	Screw Included	Screw Diameter (Sc)	Screw Length (L)
ZEA104	387540	3535426	6	No		
ZE104	313040	1340571	6	Yes	10	25mm
ZEA104S6	387542		6	No		

DIAGRAMS



WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

North America

+1.800.753.9221

Option 1 – Customer Care

Option 2 – Technical

Support

Europe

Netherlands:

+31 800-0200135

France:

+33 800 901 793

Europe

Germany:

800 1890272

Other Countries:

+31 13 5835404

APAC

Shanghai:

+ 86 21 2412 1618/19

Sydney:

+61 2 9751 8500



Our powerful portfolio of brands:

CADDY

ERICO

HOFFMAN

ILSCO

SCHROFF

TRACHTE

