

Friction Slide, L



These profiles should be used to support heavy equipment and to relieve forces from the 19" profile brackets.

FEATURES

Description: To support heavy components which are only fitted to the front. Mounted between two 19" profiles. Version fixed with 2 screws per profile, and version with click-in fixation.

Material: Click-in version 1.5 mm and mounted version 3 mm zinc plated steel.

Pack quantity: 1 pair with fixing material.

SPECIFICATIONS

Thickness: 3mm
Material: Mild Steel
Finish: Plated

Table 1/1

Catalog Number	E-Number	Height	Width	Depth	Max Load	Enclosure Material
L470	2411519	43mm	470mm	42mm	980N	Mild Steel
L406C	2411518	43mm	406mm	42mm	490N	Mild Steel
L470C	2411520	43mm	470mm	42mm	490N	Mild Steel
L700	2411522	43mm	700mm	42mm	980N	Mild Steel
L406	6904656	43mm	406mm	42mm	980N	Mild Steel
L597	2411521	43mm	597mm	42mm	980N	Mild Steel
L279	2411516	43mm	279mm	42mm	980N	Mild Steel

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.



Our powerful portfolio of brands:

CADDY ERICO HOFFMAN ILSCO SCHROFF TRACHTE