

Interlock bars, FMB



This connection bar mechanically connects a system actuator with the secondary door interlocking kit, and allows the secondary door to be opened only when the primary door is opened first.

FEATURES

Description: For MCF/MCS enclosures. Interlock rods mechanically link all secondary doors to the primary door. Rod length corresponds to enclosure door width.

Material: Zinc plated steel.

Pack quantity: 5 pieces with mounting material.

SPECIFICATIONS

Thickness: 3mm
Material: Mild Steel
Finish: Zinc Plated

Table 1/1

Catalog Number	E-Number	Height	Width	Depth	Enclosure Material	Product Family
FMB1000	2415543	17mm	860mm	17mm	Mild Steel	Free-Standing
FMB800	2415546	17mm	660mm	17mm	Mild Steel	Free-Standing
FMB600	2415545	17mm	460mm	17mm	Mild Steel	Free-Standing
FMB1200	2415544	17mm	1060mm	17mm	Mild Steel	Free-Standing

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.



Our powerful portfolio of brands:

CADDY ERICO HOFFMAN ILSCO SCHROFF TRACHTE